



LV HRC fuse element, NH0, In: 160 A, gG, Un AC: 500 V, Un DC: 440 V, Front indicator, live grip lugs

Model	
product brand name	SENTRON
product designation	LV HRC fuse link
design of the product	With blade contacts
design of an identification indicator	Front indicators
design of the switching contact	Non-corroding, silver-plated
design of the fuse link	LV HRC fuse link
General technical data	
size of fuse system according to EN 60269-1	NH0
operating class of the fuse link	gG
mounting type	non-insulated grip lugs
type of voltage of the operating voltage	AC
supply voltage	
• at AC rated value	500 V
Protection class	
protection class IP	IP20, with connected conductors
Switching capacity	
switching capacity current	
• at DC according to IEC 60947-2 rated value	25 kA
• according to IEC 60947-2 rated value	120 kA
Dissipation	
power loss [W]	13.5 W
power loss [W] for rated value of the current at AC in hot operating state per pole	13.5 W
Current	
operational current	
• at 30 °C rated value	156.8 A
• at 40 °C rated value	152 A
• at 45 °C rated value	147.2 A
• at 50 °C rated value	144 A
• at 55 °C rated value	140.8 A
• at 60 °C rated value	137.6 A
• at AC rated value	160 A
Mechanical Design	
width of the enclosure	30 mm
mounting position	Any, preferably vertical
net weight	272 g
Environmental conditions	
ambient temperature during operation	
• minimum	-5 °C

- maximum

environmental category  
environmental category during storage

40 °C  
-20 to +50 at 95% relative humidity  
90% at 20°C

#### General Product Approval

#### Declaration of Conformity



[Confirmation](#)



#### Test Certificates

#### Marine / Shipping

#### other

[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)

[Miscellaneous](#)



[Miscellaneous](#)

[Environmental Confirmations](#)

#### other

[Miscellaneous](#)

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NA3036>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3NA3036>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**



[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NA3036](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NA3036)

**CAX-Online-Generator**


<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



**F**



# FU

