



LV HRC fuse element, NH000, In: 25 A, gG, Un AC: 690 V, Un DC: 250 V, Front indicator, live grip lugs

Model			
product brand name	SETRON		
product designation	LV HRC fuse link		
design of the product	With blade contacts		
design of an identification indicator	Front indicators		
design of the switching contact	Non-corroding, silver-plated		
design of the fuse link	LV HRC fuse link		
General technical data			
size of fuse system according to EN 60269-1	NH000		
operating class of the fuse link	gG		
mounting type	non-insulated grip lugs		
type of voltage of the operating voltage	AC/DC		
supply voltage			
• at AC rated value			690 V
• at DC			250 V
Protection class			
protection class IP	IP20, with connected conductors		
Switching capacity			
switching capacity current			
• at DC according to IEC 60947-2 rated value			25 kA
• according to IEC 60947-2 rated value			120 kA
Dissipation			
power loss [W]	2.7 W		
power loss [W] for rated value of the current at AC in hot operating state per pole	2.7 W		
Mechanical Design			
width of the enclosure	21 mm		
mounting position	Any, preferably vertical		
net weight	128 g		
Environmental conditions			
ambient temperature during operation			
• minimum			-5 °C
• maximum			40 °C
environmental category	-20 to +50 at 95% relative humidity		
environmental category during storage	90% at 20°C		
Certificates			
reference code according to IEC 81346-2	FC		
General Product Approval		Declaration of Conformity	

[Confirmation](#)



Test Certificates	Marine / Shipping	other
-------------------	-------------------	-------

[Special Test Certificate](#)

[Miscellaneous](#)

[Type Test Certificates/Test Report](#)



[Confirmation](#)

[Miscellaneous](#)

other	Environment
-------	-------------

[Miscellaneous](#)

[Environmental Confirmations](#)

Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NA3810-6>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NA3810-6>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)



http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NA3810-6

CAX-Online-Generator


<http://www.siemens.com/cax>

Tender specifications


<http://www.siemens.com/specifications>



-F



FU



last modified:

2/14/2023 

