



SITOR cylindrical fuse link, 10 x 38 mm, 12 A, aR, Un AC: 600 V, Un DC: 700 V, DC according to UL

Model		
product brand name	SENTRON	
product designation	SITOR cylindrical fuse link	
design of the product	DC acc. to UL	
General technical data		
operating class of the fuse link	aR	
size of the fuse link	10x38 mm	
type of voltage of the operating voltage	AC	
supply voltage at DC	700 V	
operating voltage at AC rated value	600 V	
Dissipation		
power loss [W] for rated value of the current at AC in hot operating state per pole	3 W	
operational current at AC rated value	12 A	
Main circuit		
operational current rated value	12 A	
Product details		
product component striker	No	
Mechanical Design		
mounting position	Any, preferably vertical	
net weight	9 g	
General Product Approval		Declaration of Conformity



[Confirmation](#)



Declaration of Conformity	other
---------------------------	-------



[Miscellaneous](#)

[Environmental Confirmations](#)

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NC1012>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NC1012>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC1012

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



