



SITOR cylindrical fuse link, 10 x 38 mm, 20 A, aR, Un AC: 600 V, Un DC: 700 V, DC according to UL

Model		
product brand name		SENTRON
product designation		SITOR cylindrical fuse link
design of the product		DC acc. to UL
General technical data		
operating class of the fuse link		aR
size of the fuse link		10x38 mm
type of voltage of the operating voltage		AC
supply voltage at DC		700 V
operating voltage at AC rated value		600 V
Dissipation		
power loss [W] for rated value of the current at AC in hot operating state per pole		4.8 W
operational current at AC rated value		20 A
Main circuit		
operational current rated value		20 A
Product details		
product component striker		No
Mechanical Design		
mounting position		Any, preferably vertical
net weight		9 g
General Product Approval		Declaration of Conformity



[Confirmation](#)



Declaration of Conformity	other
---------------------------	-------



[Miscellaneous](#)

[Environmental Confirmations](#)

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NC1020>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NC1020>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC1020

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



