



SITOR cylindrical fuse link, 22x58 mm, 63 A, aR, Un AC: 690 V, Un DC: 700 V, DC according to UL

| Model                                                                               |                             |                           |
|-------------------------------------------------------------------------------------|-----------------------------|---------------------------|
| product brand name                                                                  | SENTRON                     |                           |
| product designation                                                                 | SITOR cylindrical fuse link |                           |
| design of the product                                                               | DC acc. to UL               |                           |
| General technical data                                                              |                             |                           |
| operating class of the fuse link                                                    | aR                          |                           |
| size of the fuse link                                                               | 22x58 mm                    |                           |
| type of voltage of the operating voltage                                            | AC                          |                           |
| supply voltage at DC                                                                | 700 V                       |                           |
| operating voltage at AC rated value                                                 | 690 V                       |                           |
| Dissipation                                                                         |                             |                           |
| power loss [W] for rated value of the current at AC in hot operating state per pole | 11 W                        |                           |
| operational current at AC rated value                                               | 63 A                        |                           |
| Main circuit                                                                        |                             |                           |
| operational current rated value                                                     | 63 A                        |                           |
| Product details                                                                     |                             |                           |
| product component striker                                                           | No                          |                           |
| Mechanical Design                                                                   |                             |                           |
| mounting position                                                                   | Any, preferably vertical    |                           |
| net weight                                                                          | 57 g                        |                           |
| General Product Approval                                                            |                             | Declaration of Conformity |



[Confirmation](#)



other

[Environmental Con-  
firmations](#)

[Miscellaneous](#)

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)  
<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NC2263>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NC2263>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NC2263](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC2263)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



