



SITOR fuse link, with female thread on both sides, NH3, In: 800 A, aR, Un AC: 1100 V, Un DC: 440 V, front indicator

Model		
product brand name		SETRON
product designation		SITOR fuse link
design of the product		With female thread on both sides
design of an identification indicator		front indicator
design of the fuse link		SITOR, LV HRC design
General technical data		
size of fuse system according to EN 60269-1		NH3
operating class of the fuse link		aR
varying load factor (WL)		0.95
type of voltage of the operating voltage		AC/DC
operating voltage at AC according to UL rated value		1 100 V
Supply voltage		
supply voltage		
• at AC rated value		1 100 V
• at DC		440 V
Switching capacity		
switching capacity current		
• according to IEC 60947-2 rated value		100 kA
Dissipation		
power loss [W]		145 W
power loss [W]		
• for rated value of the current at AC in hot operating state per pole		145 W
• maximum		145 W
Mechanical Design		
mounting position		Any, preferably vertical
net weight		995 g
Environmental conditions		
ambient temperature during operation		
• minimum		-20 °C
• maximum		50 °C
environmental category		-20 to +50 at 95% relative humidity
General Product Approval		Declaration of Con- formity
		other

[Confirmation](#)



[Confirmation](#)

[Miscellaneous](#)

Environment

[Environmental Con-
firmations](#)

Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NC3438-6U>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NC3438-6U>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC3438-6U

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

last modified:

2/3/2023 

