


















Fuseless motor starter Direct start 600VAC Size S2 35-45Amp 110/120VAC 50/60HZ screw connection For screw mounting Or 35 mm rail-mounting Type of coordination 2 IQ = 150 KA Also full fills type Of coordination 1 1NO+1NC (MSP) 1NO+1NC (contactor)

product brand name	SIRIUS
product designation	non-fused motor starter 3RA2
design of the product	direct starter
manufacturer's article number	
• of the supplied contactor	<a href="#">3RT2036-1AK60</a>
• of the supplied circuit-breakers	<a href="#">3RV2032-4VA15</a>
• of the supplied link module	<a href="#">3RA2931-1AA00</a>
<b>General technical data</b>	
size of the circuit-breaker	S2
size of load feeder	S2
product extension auxiliary switch	Yes
insulation voltage with degree of pollution 3 at AC rated value	690 V
degree of pollution	3
surge voltage resistance rated value	6 kV
shock resistance according to IEC 60068-2-27	6g / 11 ms
mechanical service life (operating cycles) of contactor typical	10 000 000
type of assignment	2
<b>Ambient conditions</b>	
ambient temperature	
• during operation	-20 ... +60 °C
• during storage	-50 ... +80 °C
• during transport	-55 ... +80 °C
<b>Main circuit</b>	
number of poles for main current circuit	3
design of the switching contact	electromechanical
adjustable current response value current of the current-dependent overload release	35 ... 45 A
operating voltage	
• rated value	690 V
• at AC-3 rated value maximum	690 V
operating frequency rated value	50 ... 60 Hz
operational current at AC-3 at 400 V rated value	41 A
operating power at AC-3	
• at 400 V rated value	22 000 W
<b>Control circuit/ Control</b>	
control supply voltage at AC	
• at 50 Hz rated value	110 V
• at 50 Hz rated value	88 ... 121 V
• at 60 Hz rated value	120 V
• at 60 Hz rated value	96 ... 132 V
apparent holding power of magnet coil at AC	16 VA
inductive power factor with the holding power of the coil	0.37
<b>Auxiliary circuit</b>	
number of NC contacts for auxiliary contacts	2
number of NO contacts for auxiliary contacts	2
<b>Protective and monitoring functions</b>	
trip class	CLASS 10
design of the overload release	thermal (bimetallic)
response value current of instantaneous short-circuit trip unit	585 A

UL/CSA ratings																			
yielded mechanical performance [hp]		3 hp																	
<ul style="list-style-type: none"><li>for single-phase AC motor<ul style="list-style-type: none"><li>at 110/120 V rated value</li></ul></li></ul>																			
Short-circuit protection																			
product function short circuit protection		Yes																	
design of the short-circuit trip		magnetic																	
conditional short-circuit current (I <sub>q</sub> )		150 000 A																	
<ul style="list-style-type: none"><li>at 400 V according to IEC 60947-4-1 rated value</li></ul>																			
Installation/ mounting/ dimensions																			
mounting position		vertical																	
fastening method		Snap-mounted to DIN rail or screw-mounted with additional push-in lug																	
height		274 mm																	
width		55 mm																	
depth		150 mm																	
required spacing																			
<ul style="list-style-type: none"><li>for grounded parts<ul style="list-style-type: none"><li>forwards</li><li>backwards</li><li>upwards</li><li>at the side</li><li>downwards</li></ul></li></ul>																			
<ul style="list-style-type: none"><li>for live parts<ul style="list-style-type: none"><li>forwards</li><li>backwards</li><li>upwards</li><li>downwards</li><li>at the side</li></ul></li></ul>																			
Connections/ Terminals																			
type of electrical connection for main current circuit		screw-type terminals																	
type of connectable conductor cross-sections for main contacts stranded		1 ... 50 mm², 2x (1 ... 25 mm²)																	
connectable conductor cross-section for main contacts finely stranded with core end processing		1 ... 35 mm²																	
Safety related data																			
B10 value with high demand rate according to SN 31920		1 000 000																	
proportion of dangerous failures with high demand rate according to SN 31920		73 %																	
protection class IP on the front according to IEC 60529		IP20																	
touch protection on the front according to IEC 60529		finger-safe, for vertical contact from the front																	
Certificates/ approvals																			
General Product Approval		For use in hazard- ous locations	Declaration of Conformity																
<div><div><a href="#">Confirmation</a></div><div></div></div> <div></div> <div><div></div><div>ATEX</div></div> <div></div> <div><div></div><div>EG-Konf.</div></div> <tr><th colspan="2">Test Certificates</th><th colspan="2">Marine / Shipping</th></tr> <tr><td colspan="2"><div><a href="#">Special Test Certificate</a></div><div><a href="#">Type Test Certificates/Test Report</a></div></td><td colspan="2"><div></div><div></div><div></div><div></div></td></tr> <tr><td colspan="2">Marine / Shipping</td><td>other</td><td>Railway</td></tr> <tr><td colspan="2"></td><td></td><td>Dangerous Good</td></tr>				Test Certificates		Marine / Shipping		<div><a href="#">Special Test Certificate</a></div> <div><a href="#">Type Test Certificates/Test Report</a></div>		<div></div> <div></div> <div></div> <div></div>		Marine / Shipping		other	Railway				Dangerous Good
Test Certificates		Marine / Shipping																	
<div><a href="#">Special Test Certificate</a></div> <div><a href="#">Type Test Certificates/Test Report</a></div>		<div></div> <div></div> <div></div> <div></div>																	
Marine / Shipping		other	Railway																
			Dangerous Good																

[Confirmation](#)[Vibration and Shock](#)[Transport Information](#)

#### Further information

**Siemens has decided to exit the Russian market (see here).**

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

**Siemens is working on the renewal of the current EAC certificates.**

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

**Information on the packaging**

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RA2155-4VA36-0AK6>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA2155-4VA36-0AK6>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3RA2155-4VA36-0AK6>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RA2155-4VA36-0AK6&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA2155-4VA36-0AK6&lang=en)

**Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current**

<https://support.industry.siemens.com/cs/ww/en/ps/3RA2155-4VA36-0AK6/char>

**Further characteristics (e.g. electrical endurance, switching frequency)**

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RA2155-4VA36-0AK6&objecttype=14&gridview=view1>

last modified:

12/15/2020