## **SIEMENS**

3RA2932-2G **Data sheet** 

> mechanical connectors for contactor combinations, 20 mm contactor clearance, for 10 combinations, (2 connectors for each combination), for contactors 3RT233



product brand name	SIRIUS
product designation	Mechanical connectors
design of the product	for contactor assemblies size S2/S2, 4-pole for reversing, contactor clearance 20 mm
Substance Prohibitance (Date)	10/01/2014
Further information	

Siemens has decided to exit the Russian market (see here).

<u>rind-down-russian-business</u>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RA2932-2G

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA2932-2G

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3RA2932-2

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)


http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3RA2932-2G&lang=en


Characteristic: Tripping characteristics, I2t, Let-through current

https://support.industry.siemens.com/cs/ww/en/ps/3RA2932

Further characteristics (e.g. electrical endurance, switching frequency)

http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RA2932-2G&objecttype=14&gridview=view1





last modified: 12/21/2020 🖸