



Semiconductor relay, 1-phase 3RF2 Width 22.5 mm, 20 A 24-230 V / 4-30 V DC Spring-type terminal

product brand name	SIRIUS
product designation	solid-state relay
design of the product	single-phase
product type designation	3RF21
manufacturer's article number	
<ul style="list-style-type: none">• _3 of the accessories that can be ordered	3RF2900-0EA18
product designation	
<ul style="list-style-type: none">• _3 of the accessories that can be ordered	converter








General technical data

product function	zero-point switching
power loss [V·A] maximum	28.6 VA
power loss [W] for rated value of the current	
<ul style="list-style-type: none">• at AC in hot operating state	28.6 W
<ul style="list-style-type: none">• at AC in hot operating state per pole	28.6 W
<ul style="list-style-type: none">• without load current share typical	0.5 W
insulation voltage rated value	600 V
type of voltage of the control supply voltage	DC
surge voltage resistance of main circuit rated value	6 kV
shock resistance according to IEC 60068-2-27	15g / 11 ms
vibration resistance according to IEC 60068-2-6	2g
reference code according to IEC 81346-2	Q
Substance Prohibitance (Date)	05/28/2009

Main circuit

number of poles for main current circuit	1
number of NO contacts for main contacts	1
number of NC contacts for main contacts	0
operating voltage at AC	
<ul style="list-style-type: none">• at 50 Hz rated value	24 ... 230 V
<ul style="list-style-type: none">• at 60 Hz rated value	24 ... 230 V
operating frequency rated value	50 ... 60 Hz
relative symmetrical tolerance of the operating frequency	10 %
operating range relative to the operating voltage at AC	
<ul style="list-style-type: none">• at 50 Hz	20 ... 253 V
<ul style="list-style-type: none">• at 60 Hz	20 ... 253 V
operational current	
<ul style="list-style-type: none">• at AC-51 rated value	20 A
<ul style="list-style-type: none">• according to UL 508 rated value	20 A
ampacity maximum	20 A
operational current minimum	100 mA
rate of voltage rise at the thyristor for main contacts	500 V/μs
maximum permissible	

blocking voltage at the thyristor for main contacts maximum permissible	800 V
reverse current of the thyristor	10 mA
derating temperature	40 °C
surge current resistance rated value	200 A
I²t value maximum	200 A ² ·s
Control circuit/ Control	
type of voltage of the control supply voltage	DC
control supply voltage 1	
• at DC rated value	30 V
• at DC	4 ... 30 V
control supply voltage	
• at DC initial value for signal <1> detection	4 V
• at DC full-scale value for signal<0> recognition	1 V
control current at minimum control supply voltage	
• at DC	13 mA
control current at DC rated value	15 mA
ON-delay time	1 ms; additionally max. one half-wave
OFF-delay time	1 ms; additionally max. one half-wave
Auxiliary circuit	
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	0
number of CO contacts for auxiliary contacts	0
Installation/ mounting/ dimensions	
fastening method	screw fixing
• side-by-side mounting	Yes
design of the thread of the screw for securing the equipment	M4
tightening torque of fixing screw maximum	1.5 N·m
tightening torque [lbf·in] of fixing screw maximum	13 lbf·in
height	85 mm
width	22.5 mm
depth	48 mm
Connections/ Terminals	
type of electrical connection	
• for main current circuit	spring-loaded terminals
• for auxiliary and control circuit	spring-loaded terminals
type of connectable conductor cross-sections	
• for main contacts	
— solid	2x (0.5 ... 2.5 mm ²)
— finely stranded with core end processing	2x (0.5 ... 1.5 mm ²)
— finely stranded without core end processing	2x (0.5 ... 2.5 mm ²)
• at AWG cables for main contacts	2x (18 ... 14)
connectable conductor cross-section for main contacts	
• solid or stranded	0.5 ... 2.5 mm ²
• finely stranded with core end processing	0.5 ... 1.5 mm ²
• finely stranded without core end processing	0.5 ... 2.5 mm ²
type of connectable conductor cross-sections	
• for auxiliary and control contacts	
— solid	0.5 ... 1.5 mm ²
— finely stranded with core end processing	0.5 ... 2.5 mm ²
— finely stranded without core end processing	0.5 ... 2.5 mm ²
• at AWG cables for auxiliary and control contacts	1x (AWG 20 ... 12)
AWG number as coded connectable conductor cross section for main contacts	14 ... 10
tightening torque	
• for main contacts with screw-type terminals	2 ... 2.5 N·m
stripped length of the cable	
• for main contacts	10 mm
• for auxiliary and control contacts	10 mm
Safety related data	
protection class IP on the front according to IEC 60529	IP20

touch protection on the front according to IEC 60529		finger-safe, for vertical contact from the front			
Ambient conditions					
installation altitude at height above sea level maximum		1 000 m			
ambient temperature					
• during operation		-25 ... +60 °C			
• during storage		-55 ... +80 °C			
Electromagnetic compatibility					
conducted interference					
• due to burst according to IEC 61000-4-4		2 kV / 5 kHz behavior criterion 2			
• due to conductor-earth surge according to IEC 61000-4-5		2 kV behavior criterion 2			
• due to conductor-conductor surge according to IEC 61000-4-5		1 kV behavior criterion 2			
• due to high-frequency radiation according to IEC 61000-4-6		140 dBuV in the frequency range 0.15 ... 80 MHz, behavior criterion 1			
field-based interference according to IEC 61000-4-3		80 MHz ... 1 GHz 10 V/m, behavior criterion 1			
electrostatic discharge according to IEC 61000-4-2		4 kV contact discharging / 8 kV air discharging, behavior criterion 2			
conducted HF interference emissions according to CISPR11		Class A for industrial environment			
field-bound HF interference emission according to CISPR11		Class B for the domestic, business and commercial environments			
Short-circuit protection, design of the fuse link					
manufacturer's article number					
• of gS fuse for semiconductor protection at NH design usable		3NE1814-0			
• of full range R fuse link for semiconductor protection at cylindrical design usable		5SE1325			
• of back-up R fuse link for semiconductor protection at NH design usable		3NE8015-1			
• of back-up R fuse link for semiconductor protection at cylindrical design 10 x 38 mm usable		3NC1032			
• of back-up R fuse link for semiconductor protection at cylindrical design 14 x 51 mm usable		3NC1430			
• of back-up R fuse link for semiconductor protection at cylindrical design 22 x 58 mm usable		3NC2225			
manufacturer's article number of the gG fuse					
• at NH design usable		3NA6803 ; These fuses have a smaller rated current than the semiconductor relays			
• at cylindrical design 10 x 38 mm usable		3NW6001-1 ; These fuses have a smaller rated current than the semiconductor relays			
• at cylindrical design 14 x 51 mm usable		3NW6101-1 ; These fuses have a smaller rated current than the semiconductor relays			
manufacturer's article number					
• of NEOZED fuse usable		5SE2306 ; These fuses have a smaller rated current than the semiconductor relays			
Certificates/ approvals					
General Product Approval		EMC	Declaration of Conformity		
	Confirmation				
Declaration of Conformity		Test Certificates	other	Railway	
		Type Test Certificates/Test Report	Special Test Certificate	Confirmation	Vibration and Shock
					
Further information					

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RF2120-2AA42>

Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RF2120-2AA42>



Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RF2120-2AA42>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RF2120-2AA42&lang=en





last modified:

1/12/2022