



Solid-state contactor 1-phase 3RF2 AC 51 / 70 A / 40 °C 48-460 V / 24 V
DC Ring cable connection Since 21 May 2018, the dimensions and the drill pattern have changed, additional information in the Industry Online Support

product brand name

SIRIUS

product designation

solid-state contactor

design of the product

single-phase

product type designation

3RF23

manufacturer's article number

- _1 of the accessories that can be ordered
- _3 of the accessories that can be ordered
- _4 of the accessories that can be ordered

[3RF2900-3PA88](#)

[3RF2900-0EA18](#)

[3RF2990-0GA16](#)

product designation

- _1 of the accessories that can be ordered
- _3 of the accessories that can be ordered
- _4 of the accessories that can be ordered

terminal cover

converter

load monitoring

General technical data

product function

zero-point switching

power loss [W] for rated value of the current

- at AC in hot operating state
- at AC in hot operating state per pole
- without load current share typical

83 W

83 W

0.4 W

insulation voltage rated value

600 V

degree of pollution

3

type of voltage of the control supply voltage

DC

surge voltage resistance of main circuit rated value

6 kV

shock resistance according to IEC 60068-2-27

15g / 11 ms

vibration resistance according to IEC 60068-2-6

2g

reference code according to IEC 81346-2

Q

Substance Prohibitance (Date)

07/01/2006

Main circuit

number of poles for main current circuit

1

number of NO contacts for main contacts

1

number of NC contacts for main contacts

0

operating voltage at AC

- at 50 Hz rated value
- at 60 Hz rated value

48 ... 460 V

48 ... 460 V

operating frequency rated value

50 ... 60 Hz

operating range relative to the operating voltage at AC

- at 50 Hz
- at 60 Hz

40 ... 506 V

40 ... 506 V

operational current

- at AC-51 rated value
- at AC-51 according to IEC 60947-4-3
- according to UL 508 rated value




70 A



70 A

62 A

operational current minimum	500 mA
rate of voltage rise at the thyristor for main contacts maximum permissible	1 000 V/μs
blocking voltage at the thyristor for main contacts maximum permissible	1 200 V
reverse current of the thyristor	10 mA
derating temperature	40 °C
surge current resistance rated value	1 150 A
I ² t value maximum	6 600 A ² ·s
Control circuit/ Control	
type of voltage of the control supply voltage	DC
control supply voltage 1	30 V
• at DC rated value	15 ... 24 V
• at DC	
control supply voltage	15 V
• at DC initial value for signal <1> detection	5 V
• at DC full-scale value for signal<0> recognition	
control current at minimum control supply voltage	13 mA
• at DC	15 mA
control current at DC rated value	1 ms; additionally max. one half-wave
ON-delay time	1 ms; additionally max. one half-wave
OFF-delay time	
Auxiliary circuit	
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	0
number of CO contacts for auxiliary contacts	0
Installation/ mounting/ dimensions	
fastening method	screw fixing and snap-on mounting on standard mounting rail 35 mm according to IEC 60715
• side-by-side mounting	Yes
design of the thread of the screw for securing the equipment	M4
height	100 mm
width	80 mm
depth	162 mm
Connections/ Terminals	
type of electrical connection	Ring cable lug connection ring terminal lug connection
• for main current circuit	
• for auxiliary and control circuit	
type of connectable conductor cross-sections	JIS C 2805 R 2-5, 5,5-5, 8-5, 14-5 DIN 46234 -5-2,5, -5-6, -5-10, -5-16, -5-25
• for main contacts for JIS cable lug	
• for DIN cable lug for main contacts	
type of connectable conductor cross-sections	
• for auxiliary and control contacts	
— solid	1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²)
— finely stranded with core end processing	1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²)
— finely stranded without core end processing	1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²)
• at AWG cables for auxiliary and control contacts	1x (AWG 20 ... 12)
tightening torque	2 ... 2.5 N·m
• for main contacts with screw-type terminals	0.5 ... 0.6 N·m
• for auxiliary and control contacts with screw-type terminals	
tightening torque [lbf·in]	4.5 ... 5.3 lbf·in
• for auxiliary and control contacts with screw-type terminals	
design of the thread of the connection screw	M5
• for main contacts	M3
• of the auxiliary and control contacts	
stripped length of the cable	10 mm
• for main contacts	10 mm
• for auxiliary and control contacts	
Safety related data	
protection class IP on the front according to IEC 60529	IP00; IP20 with cover

touch protection on the front according to IEC 60529		finger-safe, for vertical contact from the front with cover			
Ambient conditions					
installation altitude at height above sea level maximum		1 000 m			
ambient temperature					
• during operation		-25 ... +60 °C			
• during storage		-55 ... +80 °C			
Electromagnetic compatibility					
conducted interference					
• due to burst according to IEC 61000-4-4		2 kV / 5 kHz behavior criterion 2			
• due to conductor-earth surge according to IEC 61000-4-5		2 kV behavior criterion 2			
• due to conductor-conductor surge according to IEC 61000-4-5		1 kV behavior criterion 2			
• due to high-frequency radiation according to IEC 61000-4-6		140 dBuV in the frequency range 0.15 ... 80 MHz, behavior criterion 1			
field-based interference according to IEC 61000-4-3		80 MHz ... 1 GHz 10 V/m, behavior criterion 1			
electrostatic discharge according to IEC 61000-4-2		4 kV contact discharging / 8 kV air discharging, behavior criterion 2			
conducted HF interference emissions according to CISPR11		Class A for industrial environment			
field-bound HF interference emission according to CISPR11		Class B for the domestic, business and commercial environments			
Short-circuit protection, design of the fuse link					
manufacturer's article number					
• of full range R fuse link for semiconductor protection at NH design usable		3NE1020-2			
• of back-up R fuse link for semiconductor protection at NH design usable		3NE8020-1			
• of back-up R fuse link for semiconductor protection at cylindrical design 22 x 58 mm usable		3NC2280			
manufacturer's article number					
• of NEOZED fuse usable		5SE2335 ; These fuses have a smaller rated current than the semiconductor relays			
Certificates/ approvals					
General Product Approval		EMC	Declaration of Conformity		
	Confirmation				
Declaration of Conformity		Test Certificates		other	
	Type Test Certificates/Test Report	Confirmation			
Further information					
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875					
Information- and Downloadcenter (Catalogs, Brochures,...) https://www.siemens.com/ic10					
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RF2370-3AA04					
Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RF2370-3AA04					
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3RF2370-3AA04					
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RF2370-3AA04&lang=en					





last modified:

1/26/2022