



extended load monitoring current range 90 A / 40 °C 400 ... 600 V / 110 V  
AC for semiconductor relay / contactor

<b>product brand name</b>	SIRIUS
<b>product designation</b>	extended load monitoring
<b>manufacturer's article number</b>	
• _1 of the accessories that can be ordered	<a href="#">3RF2900-0RA88</a>
<b>product designation</b>	
• _1 of the accessories that can be ordered	sealable end cover

### General technical data

<b>product function</b>	solid-state relay / solid-state contactor 3RF2
<b>power loss [W] for rated value of the current</b>	
• without load current share typical	2.2 W
<b>insulation voltage rated value</b>	600 V
<b>degree of pollution</b>	3
<b>surge voltage resistance of main circuit rated value</b>	2.5 kV
<b>shock resistance according to IEC 60068-2-27</b>	15g / 11 ms
<b>vibration resistance according to IEC 60068-2-6</b>	2g
<b>design of the switching function</b>	CO contact
<b>reference code according to IEC 81346-2</b>	B
<b>Substance Prohibitance (Date)</b>	05/01/2012

### Main circuit

<b>number of poles for main current circuit</b>	0
<b>number of NO contacts for main contacts</b>	0
<b>number of NC contacts for main contacts</b>	0
<b>type of voltage</b>	AC
<b>operating voltage at AC</b>	
• at 50 Hz rated value	400 ... 600 V
• at 60 Hz rated value	400 ... 600 V
<b>operating frequency rated value</b>	50 ... 60 Hz
<b>relative symmetrical tolerance of the operating frequency</b>	10 %
<b>operating range relative to the operating voltage at AC</b>	
• at 50 Hz	340 ... 660 V
• at 60 Hz	340 ... 660 V
<b>operational current</b>	
• at AC-51 rated value	90 A
<b>derating temperature</b>	40 °C

### Control circuit/ Control

<b>type of voltage</b>	AC
<b>control supply voltage at AC</b>	
• at 50 Hz rated value	90 ... 121 V
• at 60 Hz rated value	90 ... 121 V
<b>control supply voltage 1 at AC</b>	

<ul style="list-style-type: none"><li>• at 50 Hz</li></ul>	110 V	
<b>control supply voltage at AC</b>		
<ul style="list-style-type: none"><li>• at 50 Hz full-scale value for signal&lt;0&gt; recognition</li><li>• at 60 Hz full-scale value for signal&lt;0&gt; recognition</li></ul>	15 V 15 V	
<b>supply voltage frequency for auxiliary and control circuit rated value</b>	50 ... 60 Hz	
<b>symmetrical line frequency tolerance</b>	5 Hz	
<b>control current at minimum control supply voltage</b>		
<ul style="list-style-type: none"><li>• at AC</li></ul>	2 mA	
control current at AC rated value	20 mA	
<b>Auxiliary circuit</b>		
<b>number of NC contacts for auxiliary contacts</b>	1	
<b>number of NO contacts for auxiliary contacts</b>	1	
number of CO contacts for auxiliary contacts	1	
<b>Installation/ mounting/ dimensions</b>		
<b>fastening method</b>	clip-on	
<ul style="list-style-type: none"><li>• side-by-side mounting</li></ul>	Yes	
<b>height</b>	111.5 mm	
<b>width</b>	45 mm	
<b>depth</b>	69.5 mm	
<b>Connections/ Terminals</b>		
<b>type of electrical connection</b>	screw-type terminals	
<ul style="list-style-type: none"><li>• for auxiliary and control circuit</li></ul>		
<b>type of connectable conductor cross-sections</b>		
<ul style="list-style-type: none"><li>• for auxiliary and control contacts<ul style="list-style-type: none"><li>— solid</li><li>— finely stranded with core end processing</li><li>— finely stranded without core end processing</li></ul></li><li>• at AWG cables for auxiliary and control contacts</li></ul>	1x (0.5 ... 2.5 mm²), 2x (0.5 ... 1.0 mm²) 1x (0.5 ... 2.5 mm²), 2x (0.5 ... 1.0 mm²) 1x (0.5 ... 2.5 mm²), 2x (0.5 ... 1.0 mm²) 1x (AWG 20 ... 12)	
tightening torque for auxiliary and control contacts with screw-type terminals	0.5 ... 0.6 N·m	
tightening torque [lbf·in] for auxiliary and control contacts with screw-type terminals	4.5 ... 5.3 lbf·in	
design of the thread of the connection screw of the auxiliary and control contacts	M3	
stripped length of the cable for auxiliary and control contacts	7 mm	
<b>Safety related data</b>		
<b>protection class IP on the front according to IEC 60529</b>	IP20	
<b>touch protection on the front according to IEC 60529</b>	finger-safe, for vertical contact from the front	
<b>Ambient conditions</b>		
installation altitude at height above sea level maximum	1 000 m	
<b>ambient temperature</b>		
<ul style="list-style-type: none"><li>• during operation</li><li>• during storage</li></ul>	-25 ... +60 °C -55 ... +80 °C	
<b>Electromagnetic compatibility</b>		
<b>conducted interference</b>		
<ul style="list-style-type: none"><li>• due to burst according to IEC 61000-4-4</li><li>• due to conductor-earth surge according to IEC 61000-4-5</li><li>• due to conductor-conductor surge according to IEC 61000-4-5</li><li>• due to high-frequency radiation according to IEC 61000-4-6</li></ul>	2 kV / 5 kHz behavior criterion 2 2 kV behavior criterion 2  1 kV behavior criterion 2  140 dBuV in the frequency range 0.15 ... 80 MHz, behavior criterion 1	
<b>electrostatic discharge according to IEC 61000-4-2</b>	4 kV contact discharging / 8 kV air discharging, behavior criterion 2	
<b>conducted HF interference emissions according to CISPR11</b>	Class A for industrial environment	
<b>field-bound HF interference emission according to CISPR11</b>	Class B for the domestic, business and commercial environments	
<b>Certificates/ approvals</b>		
<b>General Product Approval</b>	<b>EMC</b>	<b>Declaration of Conformity</b>



[Confirmation](#)



Declaration of  
Conformity

Test Certificates

other



[Type Test Certificates/Test Report](#)

[Confirmation](#)

#### Further information

##### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RF2990-0GA36>

##### Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RF2990-0GA36>


##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RF2990-0GA36>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RF2990-0GA36&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RF2990-0GA36&lang=en)





last modified:

10/6/2021 [🔗](#)