



Solid-state contactor 3-phase 3RF3 AC 53 / 16 A / 40 °C 48-600 V / 24 V
DC 2-phase controlled Instantaneous switching screw terminal

- product brand name**
product designation
design of the product
product type designation
manufacturer's article number
- _1 of the accessories that can be ordered
 - _2 of the accessories that can be ordered
- product designation**
- _1 of the accessories that can be ordered
 - _2 of the accessories that can be ordered

SIRIUS
 solid-state contactor
 two-phase controlled
 3RF34

[3RA2921-1BA00](#)
[3RF3900-0QA88](#)

Link module
 Connection adapter

General technical data

- product function** instantaneous switching
- power loss [W] for rated value of the current**
- at AC in hot operating state 28 W
 - at AC in hot operating state per pole 9.33 W
 - without load current share typical 0.4 W
- insulation voltage rated value** 600 V
- type of voltage of the control supply voltage** DC
- surge voltage resistance of main circuit rated value** 6 kV
- shock resistance according to IEC 60068-2-27** 15g / 11 ms
- vibration resistance according to IEC 60068-2-6** 2g
- certificate of suitability** CE / UL / CSA / CCC / C-Tick (RCM)
- reference code according to IEC 81346-2** Q
- Substance Prohibitance (Date)** 05/28/2009

Main circuit

- number of poles for main current circuit** 3
- number of NO contacts for main contacts** 2
- number of NC contacts for main contacts** 0
- operating voltage at AC**
- at 50 Hz rated value 48 ... 600 V
 - at 60 Hz rated value 48 ... 600 V
- operating frequency rated value** 50 ... 60 Hz
- relative symmetrical tolerance of the operating frequency** 10 %
- operating range relative to the operating voltage at AC**
- at 50 Hz 40 ... 660 V
 - at 60 Hz 40 ... 660 V
- operational current**
- at AC-3 at 400 V rated value 16 A
 - at AC-53a at 400 V at ambient temperature 40 °C rated value 16 A
- operational current minimum** 500 mA

operating power	7.5 kW
<ul style="list-style-type: none"> at AC-3 at 400 V rated value 	1 000 V/μs
rate of voltage rise at the thyristor for main contacts maximum permissible	
blocking voltage at the thyristor for main contacts maximum permissible	1 600 V
reverse current of the thyristor	10 mA
derating temperature	40 °C
surge current resistance rated value	1 150 A
I²t value maximum	6 600 A ² ·s

Control circuit/ Control

type of voltage of the control supply voltage	DC
control supply voltage 1	24 V
<ul style="list-style-type: none"> at DC rated value 	
control supply voltage	15 V
<ul style="list-style-type: none"> at DC initial value for signal <1> detection at DC full-scale value for signal<0> recognition 	5 V
symmetrical line frequency tolerance	5 Hz
operating range factor control supply voltage rated value at DC	
<ul style="list-style-type: none"> initial value full-scale value 	0.63 1.25
control current at minimum control supply voltage	2 mA
<ul style="list-style-type: none"> at DC 	15 mA
control current at DC rated value	
ON-delay time	1 ms
OFF-delay time	1 ms; additionally max. one half-wave

Auxiliary circuit

number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	0
number of CO contacts for auxiliary contacts	0

Installation/ mounting/ dimensions

mounting position	vertical
fastening method	screw and snap-on mounting onto 35 mm DIN rail
<ul style="list-style-type: none"> side-by-side mounting 	Yes
design of the thread of the screw for securing the equipment	M4
height	95 mm
width	90 mm
depth	100.8 mm
required spacing with side-by-side mounting	
<ul style="list-style-type: none"> upwards downwards 	70 mm 50 mm

Connections/ Terminals

product component removable terminal for auxiliary and control circuit	Yes
type of electrical connection	
<ul style="list-style-type: none"> for main current circuit for auxiliary and control circuit 	screw-type terminals screw-type terminals
type of connectable conductor cross-sections	
<ul style="list-style-type: none"> for main contacts <ul style="list-style-type: none"> — solid — finely stranded with core end processing — finely stranded without core end processing at AWG cables for main contacts 	2x (0.5 ... 2.5 mm ²) 2x (0.5 ... 1.5 mm ²) 2x (0.5 ... 2.5 mm ²) 2x (18 ... 14)
connectable conductor cross-section for main contacts	
<ul style="list-style-type: none"> solid or stranded finely stranded with core end processing finely stranded without core end processing 	0.5 ... 2.5 mm ² 0.5 ... 1.5 mm ² 0.5 ... 2.5 mm ²
type of connectable conductor cross-sections	
<ul style="list-style-type: none"> for auxiliary and control contacts <ul style="list-style-type: none"> — solid — finely stranded with core end processing 	1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²) 1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²)

<ul style="list-style-type: none"> — finely stranded without core end processing • at AWG cables for auxiliary and control contacts 	1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²) 1x (AWG 20 ... 12) 14 ... 10
tightening torque <ul style="list-style-type: none"> • for main contacts with screw-type terminals • for auxiliary and control contacts with screw-type terminals 	2 ... 2.5 N·m 0.5 ... 0.6 N·m
tightening torque [lbf-in] <ul style="list-style-type: none"> • for main contacts with screw-type terminals • for auxiliary and control contacts with screw-type terminals 	18 ... 22 lbf-in 7.5 ... 5.3 lbf-in
design of the thread of the connection screw <ul style="list-style-type: none"> • for main contacts • of the auxiliary and control contacts 	M4 M3
stripped length of the cable <ul style="list-style-type: none"> • for main contacts • for auxiliary and control contacts 	7 mm 7 mm

UL/CSA ratings

full-load current (FLA) for 3-phase AC motor <ul style="list-style-type: none"> • at 480 V rated value • at 600 V rated value 	7.6 A 9 A
yielded mechanical performance [hp] for 3-phase AC motor <ul style="list-style-type: none"> • at 200/208 V rated value • at 220/230 V rated value • at 460/480 V rated value • at 575/600 V rated value 	2 hp 2 hp 5 hp 7.5 hp

Safety related data

proportion of dangerous failures with high demand rate according to SN 31920	50 %
MTTF with high demand rate	76 a
T1 value for proof test interval or service life according to IEC 61508	20 a
protection class IP on the front according to IEC 60529	IP20
touch protection on the front according to IEC 60529	finger-safe, for vertical contact from the front

Ambient conditions

installation altitude at height above sea level maximum	1 000 m
ambient temperature <ul style="list-style-type: none"> • during operation • during storage 	-25 ... +60 °C -55 ... +80 °C

Electromagnetic compatibility

conducted interference <ul style="list-style-type: none"> • due to burst according to IEC 61000-4-4 • due to conductor-earth surge according to IEC 61000-4-5 • due to conductor-conductor surge according to IEC 61000-4-5 • due to high-frequency radiation according to IEC 61000-4-6 	2 kV / 5 kHz behavior criterion 2 2 kV behavior criterion 2 1 kV behavior criterion 2 140 dBuV in the frequency range 0.15 ... 80 MHz, behavior criterion 1
electrostatic discharge according to IEC 61000-4-2	4 kV contact discharging / 8 kV air discharging, behavior criterion 2
conducted HF interference emissions according to CISPR11	Class A for industrial environment
field-bound HF interference emission according to CISPR11	Class A for industrial environment

Short-circuit protection, design of the fuse link

manufacturer's article number <ul style="list-style-type: none"> • of full range R fuse link for semiconductor protection at NH design usable • of back-up R fuse link for semiconductor protection at NH design usable • of back-up R fuse link for semiconductor protection at cylindrical design 10 x 38 mm usable • of back-up R fuse link for semiconductor protection at cylindrical design 14 x 51 mm usable 	3NE1817-0 3NE8022-1 3NC1032 3NC1450
--	--

- of back-up R fuse link for semiconductor protection at cylindrical design 22 x 58 mm usable manufacturer's article number of the gG fuse
- at NH design usable

[3NC2280](#)

[3NA3812-6](#)

Certificates/ approvals

General Product Approval

EMC



[Confirmation](#)



Declaration of Conformity

Test Certificates

other



EG-Konf.

[Type Test Certificates/Test Report](#)

[Confirmation](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RF3416-1BB06>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RF3416-1BB06>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RF3416-1BB06>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RF3416-1BB06&lang=en





