

Contactor relay, 3 NO + 1 NC, 48 V AC, 50 / 60 Hz, Size S00, screw terminal

|                                 |                     |
|---------------------------------|---------------------|
| <b>product brand name</b>       | SIRIUS              |
| <b>product designation</b>      | Auxiliary contactor |
| <b>product type designation</b> | 3RH2                |

### General technical data

|                                                                                       |                            |
|---------------------------------------------------------------------------------------|----------------------------|
| <b>size of contactor</b>                                                              | S00                        |
| product extension auxiliary switch                                                    | Yes                        |
| insulation voltage with degree of pollution 3 at AC rated value                       | 690 V                      |
| <b>degree of pollution</b>                                                            | 3                          |
| <b>surge voltage resistance rated value</b>                                           | 6 kV                       |
| <b>shock resistance at rectangular impulse</b>                                        |                            |
| • at AC                                                                               | 7,3g / 5 ms, 4,7g / 10 ms  |
| <b>shock resistance with sine pulse</b>                                               |                            |
| • at AC                                                                               | 11,4g / 5 ms, 7,3g / 10 ms |
| <b>mechanical service life (operating cycles)</b>                                     |                            |
| • of contactor typical                                                                | 30 000 000                 |
| • of the contactor with added electronically optimized auxiliary switch block typical | 5 000 000                  |
| • of the contactor with added auxiliary switch block typical                          | 10 000 000                 |
| <b>reference code according to IEC 81346-2</b>                                        | K                          |
| <b>Substance Prohibitation (Date)</b>                                                 | 10/01/2009                 |

### Ambient conditions

|                                                                       |                |
|-----------------------------------------------------------------------|----------------|
| installation altitude at height above sea level maximum               | 2 000 m        |
| <b>ambient temperature</b>                                            |                |
| • during operation                                                    | -25 ... +60 °C |
| • during storage                                                      | -55 ... +80 °C |
| <b>relative humidity minimum</b>                                      | 10 %           |
| <b>relative humidity at 55 °C according to IEC 60068-2-30 maximum</b> | 95 %           |

### Main circuit

|                                    |            |
|------------------------------------|------------|
| <b>no-load switching frequency</b> |            |
| • at AC                            | 10 000 1/h |
| • at DC                            | 10 000 1/h |

### Control circuit/ Control

|                                                                                       |              |
|---------------------------------------------------------------------------------------|--------------|
| <b>type of voltage of the control supply voltage</b>                                  | AC           |
| <b>control supply voltage at AC</b>                                                   |              |
| • at 50 Hz rated value                                                                | 48 V         |
| • at 60 Hz rated value                                                                | 48 V         |
| <b>control supply voltage frequency</b>                                               |              |
| • 1 rated value                                                                       | 50 Hz        |
| • 2 rated value                                                                       | 60 Hz        |
| <b>operating range factor control supply voltage rated value of magnet coil at AC</b> |              |
| • at 50 Hz                                                                            | 0.8 ... 1.1  |
| • at 60 Hz                                                                            | 0.85 ... 1.1 |
| <b>apparent pick-up power of magnet coil at AC</b>                                    | 37 VA        |
| <b>inductive power factor with closing power of the coil</b>                          | 0.8          |
| <b>apparent holding power of magnet coil at AC</b>                                    | 5.7 VA       |
| <b>inductive power factor with the holding power of the coil</b>                      | 0.25         |
| <b>closing delay</b>                                                                  |              |
| • at AC                                                                               | 8 ... 33 ms  |
| <b>opening delay</b>                                                                  |              |

|                                                                                                           |                                                 |
|-----------------------------------------------------------------------------------------------------------|-------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at AC</li> </ul>                                                 | 4 ... 15 ms                                     |
| <b>arcing time</b>                                                                                        | 10 ... 15 ms                                    |
| <b>Auxiliary circuit</b>                                                                                  |                                                 |
| <b>number of NC contacts for auxiliary contacts</b>                                                       | 1                                               |
| <ul style="list-style-type: none"> <li>• instantaneous contact</li> </ul>                                 | 1                                               |
| <b>number of NO contacts for auxiliary contacts</b>                                                       | 3                                               |
| <ul style="list-style-type: none"> <li>• instantaneous contact</li> </ul>                                 | 3                                               |
| <b>identification number and letter for switching elements</b>                                            | 31 E                                            |
| operational current at AC-12 maximum                                                                      | 10 A                                            |
| <b>operational current at AC-15</b>                                                                       |                                                 |
| <ul style="list-style-type: none"> <li>• at 230 V rated value</li> </ul>                                  | 10 A                                            |
| <ul style="list-style-type: none"> <li>• at 400 V rated value</li> </ul>                                  | 3 A                                             |
| <ul style="list-style-type: none"> <li>• at 500 V rated value</li> </ul>                                  | 2 A                                             |
| <ul style="list-style-type: none"> <li>• at 690 V rated value</li> </ul>                                  | 1 A                                             |
| <b>operational current at 1 current path at DC-12</b>                                                     |                                                 |
| <ul style="list-style-type: none"> <li>• at 24 V rated value</li> </ul>                                   | 10 A                                            |
| <ul style="list-style-type: none"> <li>• at 110 V rated value</li> </ul>                                  | 3 A                                             |
| <ul style="list-style-type: none"> <li>• at 220 V rated value</li> </ul>                                  | 1 A                                             |
| <ul style="list-style-type: none"> <li>• at 440 V rated value</li> </ul>                                  | 0.3 A                                           |
| <ul style="list-style-type: none"> <li>• at 600 V rated value</li> </ul>                                  | 0.15 A                                          |
| <b>operational current with 2 current paths in series at DC-12</b>                                        |                                                 |
| <ul style="list-style-type: none"> <li>• at 24 V rated value</li> </ul>                                   | 10 A                                            |
| <ul style="list-style-type: none"> <li>• at 60 V rated value</li> </ul>                                   | 10 A                                            |
| <ul style="list-style-type: none"> <li>• at 110 V rated value</li> </ul>                                  | 4 A                                             |
| <ul style="list-style-type: none"> <li>• at 220 V rated value</li> </ul>                                  | 2 A                                             |
| <ul style="list-style-type: none"> <li>• at 440 V rated value</li> </ul>                                  | 1.3 A                                           |
| <ul style="list-style-type: none"> <li>• at 600 V rated value</li> </ul>                                  | 0.65 A                                          |
| <b>operational current with 3 current paths in series at DC-12</b>                                        |                                                 |
| <ul style="list-style-type: none"> <li>• at 24 V rated value</li> </ul>                                   | 10 A                                            |
| <ul style="list-style-type: none"> <li>• at 60 V rated value</li> </ul>                                   | 10 A                                            |
| <ul style="list-style-type: none"> <li>• at 110 V rated value</li> </ul>                                  | 10 A                                            |
| <ul style="list-style-type: none"> <li>• at 220 V rated value</li> </ul>                                  | 3.6 A                                           |
| <ul style="list-style-type: none"> <li>• at 440 V rated value</li> </ul>                                  | 2.5 A                                           |
| <ul style="list-style-type: none"> <li>• at 600 V rated value</li> </ul>                                  | 1.8 A                                           |
| <b>operating frequency at DC-12 maximum</b>                                                               | 1 000 1/h                                       |
| <b>operational current at 1 current path at DC-13</b>                                                     |                                                 |
| <ul style="list-style-type: none"> <li>• at 24 V rated value</li> </ul>                                   | 10 A                                            |
| <ul style="list-style-type: none"> <li>• at 110 V rated value</li> </ul>                                  | 1 A                                             |
| <ul style="list-style-type: none"> <li>• at 220 V rated value</li> </ul>                                  | 0.3 A                                           |
| <ul style="list-style-type: none"> <li>• at 440 V rated value</li> </ul>                                  | 0.14 A                                          |
| <ul style="list-style-type: none"> <li>• at 600 V rated value</li> </ul>                                  | 0.1 A                                           |
| <b>operational current with 2 current paths in series at DC-13</b>                                        |                                                 |
| <ul style="list-style-type: none"> <li>• at 24 V rated value</li> </ul>                                   | 10 A                                            |
| <ul style="list-style-type: none"> <li>• at 60 V rated value</li> </ul>                                   | 3.5 A                                           |
| <ul style="list-style-type: none"> <li>• at 110 V rated value</li> </ul>                                  | 1.3 A                                           |
| <ul style="list-style-type: none"> <li>• at 220 V rated value</li> </ul>                                  | 0.9 A                                           |
| <ul style="list-style-type: none"> <li>• at 440 V rated value</li> </ul>                                  | 0.2 A                                           |
| <ul style="list-style-type: none"> <li>• at 600 V rated value</li> </ul>                                  | 0.1 A                                           |
| <b>operational current with 3 current paths in series at DC-13</b>                                        |                                                 |
| <ul style="list-style-type: none"> <li>• at 24 V rated value</li> </ul>                                   | 10 A                                            |
| <ul style="list-style-type: none"> <li>• at 60 V rated value</li> </ul>                                   | 4.7 A                                           |
| <ul style="list-style-type: none"> <li>• at 110 V rated value</li> </ul>                                  | 3 A                                             |
| <ul style="list-style-type: none"> <li>• at 220 V rated value</li> </ul>                                  | 1.2 A                                           |
| <ul style="list-style-type: none"> <li>• at 440 V rated value</li> </ul>                                  | 0.5 A                                           |
| <ul style="list-style-type: none"> <li>• at 600 V rated value</li> </ul>                                  | 0.26 A                                          |
| <b>operating frequency at DC-13 maximum</b>                                                               | 1 000 1/h                                       |
| design of the miniature circuit breaker for short-circuit protection of the auxiliary circuit up to 230 V | C characteristic: 6 A; 0.4 kA                   |
| <b>contact reliability of auxiliary contacts</b>                                                          | 1 faulty switching per 100 million (17 V, 1 mA) |
| <b>UL/CSA ratings</b>                                                                                     |                                                 |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                      |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| <b>contact rating of auxiliary contacts according to UL</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | A600 / Q600                                                                                                                          |
| <b>Short-circuit protection</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                      |
| design of the fuse link for short-circuit protection of the auxiliary switch required                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | fuse gL/gG: 10 A                                                                                                                     |
| <b>Installation/ mounting/ dimensions</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                      |
| <b>mounting position</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface |
| <b>fastening method</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | screw and snap-on mounting onto 35 mm DIN rail                                                                                       |
| <b>height</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 57.5 mm                                                                                                                              |
| <b>width</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 45 mm                                                                                                                                |
| <b>depth</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 73 mm                                                                                                                                |
| <b>required spacing</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                      |
| <ul style="list-style-type: none"> <li>• with side-by-side mounting <ul style="list-style-type: none"> <li>— forwards 10 mm</li> <li>— upwards 10 mm</li> <li>— downwards 10 mm</li> <li>— at the side 0 mm</li> </ul> </li> <li>• for grounded parts <ul style="list-style-type: none"> <li>— forwards 10 mm</li> <li>— upwards 10 mm</li> <li>— at the side 6 mm</li> <li>— downwards 10 mm</li> </ul> </li> <li>• for live parts <ul style="list-style-type: none"> <li>— forwards 10 mm</li> <li>— upwards 10 mm</li> <li>— downwards 10 mm</li> <li>— at the side 6 mm</li> </ul> </li> </ul> |                                                                                                                                      |
| <b>Connections/ Terminals</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                      |
| type of electrical connection for auxiliary and control circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | screw-type terminals                                                                                                                 |
| <b>type of connectable conductor cross-sections</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                      |
| <ul style="list-style-type: none"> <li>• for auxiliary contacts <ul style="list-style-type: none"> <li>— solid or stranded 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), 2x 4 mm²</li> <li>— finely stranded with core end processing 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)</li> </ul> </li> <li>• at AWG cables for auxiliary contacts 2x (20 ... 16), 2x (18 ... 14), 2x 12</li> </ul>                                                                                                                                                                                                      |                                                                                                                                      |
| <b>Safety related data</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                      |
| product function positively driven operation according to IEC 60947-5-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Yes                                                                                                                                  |
| B10 value with high demand rate according to SN 31920                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 1 000 000; With 0.3 x I <sub>e</sub>                                                                                                 |
| <b>proportion of dangerous failures</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                      |
| <ul style="list-style-type: none"> <li>• with low demand rate according to SN 31920 40 %</li> <li>• with high demand rate according to SN 31920 73 %</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                      |
| failure rate [FIT] with low demand rate according to SN 31920                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 100 FIT                                                                                                                              |
| T1 value for proof test interval or service life according to IEC 61508                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 20 a                                                                                                                                 |
| <b>protection class IP on the front according to IEC 60529</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | IP20                                                                                                                                 |
| <b>touch protection on the front according to IEC 60529</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | finger-safe, for vertical contact from the front                                                                                     |
| <b>Certificates/ approvals</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                      |
| <b>General Product Approval</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                      |



[Confirmation](#)



[KC](#)



|     |                                       |                           |                   |
|-----|---------------------------------------|---------------------------|-------------------|
| EMC | Functional Safety/Safety of Machinery | Declaration of Conformity | Test Certificates |
|-----|---------------------------------------|---------------------------|-------------------|



[Type Examination Certificate](#)



EG-Konf.

[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)

## Marine / Shipping



## Marine / Shipping

other

## Railway



[Confirmation](#)



[Vibration and Shock](#)

## Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RH2131-1AH00>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RH2131-1AH00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RH2131-1AH00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RH2131-1AH00&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RH2131-1AH00&lang=en)

Characteristic: Tripping characteristics,  $I^2t$ , Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RH2131-1AH00/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RH2131-1AH00&objecttype=14&gridview=view1>

last modified:

11/21/2022