



Figure similar

DS1-X for ET 200S Standard DOL starter expandable Setting range 2.8...4 A AC-3, 1.5 kW / 400 V Electromechanical starter for brake control module

<b>product brand name</b>	SIMATIC
<b>product designation</b>	Motor starters
<b>design of the product</b>	direct starter
<b>product type designation</b>	ET 200S

### General technical data

<b>trip class</b>	CLASS 10
<b>product function on-site operation</b>	Yes
<b>insulation voltage rated value</b>	500 V
<b>degree of pollution</b>	3 at 400 V, 2 at 500 V according to IEC60664 (IEC61131)
<b>surge voltage resistance rated value</b>	6 kV
<b>maximum permissible voltage for safe isolation between main and auxiliary circuit</b>	400 V
<b>shock resistance</b>	5g / 11 ms
<b>vibration resistance</b>	2g
<b>operating frequency maximum</b>	750 1/h
<b>mechanical service life (switching cycles) of the main contacts typical</b>	100 000
<b>type of assignment</b>	1
<b>reference code according to IEC 81346-2</b>	Q
<b>Substance Prohibitance (Date)</b>	10/26/2016
<b>product function</b>	
• direct start	Yes
• reverse starting	No
<b>product component motor brake output</b>	Yes
<b>product feature</b>	
• brake control with 230 V AC	No
• brake control with 24 V DC	No
• brake control with 180 V DC	No
• brake control with 500 V DC	No
<b>product extension braking module for brake control</b>	Yes
<b>product function short circuit protection</b>	Yes
<b>design of short-circuit protection</b>	circuit-breakers
<b>breaking capacity maximum short-circuit current (Icu)</b>	
• at 400 V rated value	50 kA

### Electromagnetic compatibility

<b>EMC emitted interference according to IEC 60947-1</b>	CISPR11, ambience A (industrial sector)
<b>EMC immunity according to IEC 60947-1</b>	corresponds to degree of severity 3, ambience A (industrial sector)
<b>conducted interference</b>	
• due to burst according to IEC 61000-4-4	2 kV on voltage supply, inputs and outputs
• due to conductor-earth surge according to IEC 61000-4-5	2 kV (U > 24 V DC)

<ul style="list-style-type: none"> <li>• due to conductor-conductor surge according to IEC 61000-4-5</li> </ul>	1 kV (U > 24 V DC)
<b>field-based interference according to IEC 61000-4-3</b>	80 MHz ... 1 GHz 10 V/m, 1.4 GHz ... 2 Hz 3 V/m, 2 GHz ... 2.7 GHz 1 V/m
<b>Safety related data</b>	
B10 value with high demand rate according to SN 31920	1 000 000
<b>proportion of dangerous failures</b>	
<ul style="list-style-type: none"> <li>• with low demand rate according to SN 31920</li> </ul>	50 %
<ul style="list-style-type: none"> <li>• with high demand rate according to SN 31920</li> </ul>	75 %
<b>failure rate [FIT]</b>	
<ul style="list-style-type: none"> <li>• with low demand rate according to SN 31920</li> </ul>	100 FIT
<b>protection class IP on the front according to IEC 60529</b>	IP20
<b>touch protection on the front according to IEC 60529</b>	finger-safe
<b>Main circuit</b>	
<b>number of poles for main current circuit</b>	3
<b>design of the switching contact</b>	electromechanical
<b>adjustable current response value current of the current-dependent overload release</b>	2.8 ... 4 A
<b>type of the motor protection</b>	bimetal
operating voltage rated value	200 ... 400 V
<b>operating frequency 1 rated value</b>	50 Hz
<b>operating frequency 2 rated value</b>	60 Hz
<b>relative positive tolerance of the operating frequency</b>	10 %
<b>relative negative tolerance of the operating frequency</b>	10 %
operating range relative to the operating voltage at AC at 50 Hz	200 ... 440 V
<b>operational current</b>	
<ul style="list-style-type: none"> <li>• at AC-3 at 400 V rated value</li> </ul>	4 A
operating power at AC-3 at 400 V rated value	1.5 kW
operating power for 3-phase motors at 400 V at 50 Hz	1.5 ... 1.5 kW
<b>Inputs/ Outputs</b>	
<b>product function</b>	
<ul style="list-style-type: none"> <li>• digital inputs parameterizable</li> </ul>	No
<ul style="list-style-type: none"> <li>• digital outputs parameterizable</li> </ul>	No
<b>number of digital inputs</b>	0
<b>number of sockets</b>	
<ul style="list-style-type: none"> <li>• for digital output signals</li> </ul>	0
<ul style="list-style-type: none"> <li>• for digital input signals</li> </ul>	0
<b>Supply voltage</b>	
<b>type of voltage of the supply voltage</b>	DC
<b>supply voltage 1 at DC</b>	24 ... 24 V
<b>supply voltage 1 at DC rated value</b>	
<ul style="list-style-type: none"> <li>• minimum permissible</li> </ul>	20.4 V
<ul style="list-style-type: none"> <li>• maximum permissible</li> </ul>	28.8 V
<b>Control circuit/ Control</b>	
<b>type of voltage of the control supply voltage</b>	DC
control supply voltage at DC rated value	20.4 ... 28.8 V
<b>control supply voltage 1</b>	
<ul style="list-style-type: none"> <li>• at DC rated value</li> </ul>	20.4 ... 28.8 V
<ul style="list-style-type: none"> <li>• at DC</li> </ul>	24 ... 24 V
<b>power loss [W] in auxiliary and control circuit</b>	
<ul style="list-style-type: none"> <li>• in switching state OFF</li> </ul>	
<ul style="list-style-type: none"> <li>— with bypass circuit</li> </ul>	0.3744 W
<ul style="list-style-type: none"> <li>— without bypass circuit</li> </ul>	0.374 W
<ul style="list-style-type: none"> <li>• in switching state ON</li> </ul>	
<ul style="list-style-type: none"> <li>— with bypass circuit</li> </ul>	4.1184 W
<ul style="list-style-type: none"> <li>— without bypass circuit</li> </ul>	4.118 W
<b>Installation/ mounting/ dimensions</b>	
<b>mounting position</b>	vertical, horizontal
<b>fastening method</b>	pluggable on terminal module
<b>height</b>	265 mm
<b>width</b>	45 mm

depth	120 mm
<b>Ambient conditions</b>	
installation altitude at height above sea level maximum	2 000 m
<b>ambient temperature</b>	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
relative humidity during operation	5 ... 95 %
<b>Communication/ Protocol</b>	
<b>protocol is supported</b>	
• PROFIBUS DP protocol	Yes
• PROFINET protocol	Yes
design of the interface PROFINET protocol	Yes
<b>product function bus communication</b>	Yes
protocol is supported AS-Interface protocol	No
<b>product function</b>	
• supports PROFenergy measured values	No
• supports PROFenergy shutdown	No
<b>address space memory of address range</b>	
• of the inputs	1 byte
• of the outputs	1 byte
<b>type of electrical connection</b>	
• of the communication interface	via backplane bus
• for communication transmission	via backplane bus
<b>Connections/ Terminals</b>	
type of electrical connection for main current circuit	screw-type terminals
<b>type of electrical connection</b>	
• 1 for digital input signals	using control module
• 2 for digital input signals	using control module
<b>type of electrical connection</b>	
• at the manufacturer-specific device interface	plug
• for main energy infeed	screw-type terminals
• for load-side outgoing feeder	Screw-type terminals
• for main energy transmission	via energy bus
• for supply voltage line-side	via backplane bus
• for supply voltage transmission	via backplane bus
<b>UL/CSA ratings</b>	
operating voltage at AC at 60 Hz according to CSA and UL rated value	600 V
<b>Certificates/ approvals</b>	
General Product Approval	
EMC	



[Confirmation](#)



For use in hazardous locations	Declaration of Conformity	other	Dangerous Good
--------------------------------	---------------------------	-------	----------------



[Confirmation](#)

[Transport Information](#)

#### Further information


Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1301-1EB00-0AA2>

Cax online generator



last modified:

12/15/2020 