



SIRIUS motor starter M200D AS-i Communication: AS-Interface DOL starter Basic Electronic switching AC-3, 0.75KW / 400 V 0.15 A...2.00 A Electronic overload protection Thermistor: THERMOCLICK / PTC without brake contact 2DI AS-i + 2DI / 1DO on device Han Q4/2 - Han Q8/0 with manual on-site operation and key-operated switch

product brand name	SIRIUS
product designation	Motor starters
design of the product	direct starter
product type designation	M200D
trip class	CLASS 10
product function	
• on-site operation	Yes
• control circuit interface to parallel wiring	No
insulation voltage rated value	500 V
degree of pollution	3
surge voltage resistance rated value	6 000 V
maximum permissible voltage for safe isolation	
• between main and auxiliary circuit	400 V
• between control and auxiliary circuit	24 V
protection class IP	IP65
shock resistance	12g / 11 ms
vibration resistance	7 mm / 2g
type of assignment	1
certificate of suitability	CE
Substance Prohibitive (Date)	07/01/2006
product function	
• direct start	Yes
• reverse starting	No
product component motor brake output	No
product feature	
• brake control with 230 V AC	No
• brake control with 400 V AC	No
• brake control with 24 V DC	No
• brake control with 180 V DC	No
• brake control with 500 V DC	No
product extension braking module for brake control	No
product function short circuit protection	Yes
design of short-circuit protection	circuit-breakers
maximum short-circuit current breaking capacity (Icu)	
• at 400 V rated value	50 000 A
• at 500 V rated value	20 000 A
EMC emitted interference according to IEC 60947-1	CISPR11, ambience A (group 2)
EMC immunity according to IEC 60947-1	corresponds to degree of severity 3, ambience A (industrial sector)
conducted interference	
• due to burst according to IEC 61000-4-4	2 kV network connection / 1 kV control connection
• due to conductor-earth surge according to IEC 61000-4-5	2 kV

SIRIUS
Motor starters
direct starter
M200D
CLASS 10
Yes
No
500 V
3
6 000 V
400 V
24 V
IP65
12g / 11 ms
7 mm / 2g
1
CE
07/01/2006
Yes
No
No
No
No
No
No
Yes
circuit-breakers
50 000 A
20 000 A
CISPR11, ambience A (group 2)
corresponds to degree of severity 3, ambience A (industrial sector)
2 kV network connection / 1 kV control connection
2 kV

• due to conductor-conductor surge according to IEC 61000-4-5	1 kV
touch protection against electrical shock	finger-safe
Main circuit	
number of poles for main current circuit	3
design of the switching contact	solid-state / thyristor / 2 phases
adjustable current response value current of the current-dependent overload release	0.15 ... 2 A
type of the motor protection	full motor protection
operating voltage rated value	200 ... 440 V
operational current	
• at AC at 400 V rated value	2 A
• at AC-3 at 400 V rated value	2 A
operating power	
• at AC-3	
— at 400 V rated value	0.75 kW
— at 500 V rated value	750 W
product function	
• digital inputs parameterizable	No
• digital outputs parameterizable	No
number of digital inputs	4
number of sockets	
• for digital output signals	1
• for digital input signals	4
number of digital outputs	1
Supply voltage	
type of voltage of the supply voltage	DC
supply voltage 1 at DC	24 V
supply voltage 1 at DC rated value	30 V
• minimum permissible	26.5 V
• maximum permissible	31.6 V
Control circuit/ Control	
type of voltage of the control supply voltage	DC
control supply voltage at DC rated value	20.4 ... 28.8 V
control supply voltage 1	
• at DC rated value	24 V
• at DC rated value	20.4 ... 28.8 V
• at DC	20.4 ... 28.8 V
control current at DC	
• in standby mode of operation	100 mA
• during operation	600 mA
power loss [W] in auxiliary and control circuit	
• in switching state OFF with bypass circuit	1.9584 W
• in switching state ON with bypass circuit	2.1888 W
Response times	
ON-delay time	25 ms
OFF-delay time	35 ms
mounting position	vertical, horizontal, flat
• recommended	horizontal
fastening method	screw fixing
height	215 mm
width	294 mm
depth	159 mm
Ambient conditions	
installation altitude at height above sea level maximum	2 000 m
ambient temperature	
• during operation	-25 ... +55 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
relative humidity during operation	10 ... 95 %
protocol is supported	
• PROFIBUS DP protocol	No
• PROFINET protocol	No

design of the interface

- AS-Interface protocol
- PROFINET protocol
- PROFIBUS DP protocol

product function bus communication

protocol is supported AS-Interface protocol

product function control circuit interface with IO link

type of electrical connection of the communication interface

type of electrical connection

- for main current circuit
- for auxiliary and control circuit

type of electrical connection

- 1 for digital input signals
- 1 for digital output signals
- 2 for digital input signals
- 3 for digital input signals
- 4 for digital input signals

type of electrical connection

- at the manufacturer-specific device interface
- for device addressing
- for supply voltage line-side

full-load current (FLA) for 3-phase AC motor at 480 V rated value

yielded mechanical performance [hp]

- for 3-phase AC motor
 - at 460/480 V rated value

operating voltage at AC at 60 Hz according to CSA and UL rated value

Yes
No
No
Yes
Yes
No
M12 plug

plug according to ISO 23570, HAN Q4/2 connector

M12 socket
M12 socket
M12 socket
M12 socket
M12 socket

optical interface
M12 plug
M12 plug
1.6 A

0.7 hp
480 V

Certificates/ approvals

General Product Approval

EMC



[Confirmation](#)



Declaration of Conformity

Test Certificates

other



[Type Test Certificates/Test Report](#)



[Confirmation](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1315-6KS71-2AA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1315-6KS71-2AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK1315-6KS71-2AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1315-6KS71-2AA0&lang=en



