

AS-Interface accessory IP68 T-distributor U_ASi and Uaux
for round cable 1 x M12 connector, 2 x M12 socket



General technical data			
Type of device design of the product Function		AS-Interface accessories M12-T distribution board T distribution M12	
Connections/ Terminals			
type of electrical connection AS interface • Connection		M12 1 x M12 connector / 2 x M12 box	
Inputs			
Inputs socket assignment		1 = AS-i "+" 2 = Uaux "-" 3=AS-i "-" 4 = Uaux "+"	
Mechanical data			
Type of mounting Contacts Load rating max	A	screw fixing 4	
Ambient conditions			
ambient temperature ambient temperature during storage degree of protection	°C °C	-25 ... +85 -25 ... +85 IP68	
Certificates/ approvals			
General Product Approval	EMC	Declaration of Conformity	Marine / Shipping

[Confirmation](#)



other

[Confirmation](#)

Further information
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures,...) https://www.siemens.com/ic10

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1901-1TR00>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1901-1TR00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK1901-1TR00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1901-1TR00&lang=en

last modified:

1/18/2021 