

Figure similar

AS-i compact module K60 digital A/B slave, 4 DI/3 DQ, IP67 4 x input, maximum 200 mA 3 x output, 2 A, 24 V DC maximal 4 A for all outputs 7 x M12 socket Y-II assignment Mounting plate 3RK1901-0CA00 must be ordered separately

General technical data

design of the product	digital I/O modules for operation in the field, IP67 - K60
Type	4 inputs / 3 outputs
design of the slave type	A/B slave
I/O configuration	7
ID/ID2 code	A/2
Number I/O sockets	7
type of electrical connection of the inputs and outputs	M12 screw-type terminals
AS interface total current input max	270 mA
operating voltage according to AS-Interface specification	26.5 ... 31.6 V
Ground terminal	PIN5 of each M12 socket is connected to the grounding wrist strap in the mounting plate using a pin
Addressing	front addressing socket
Delivery note	the modules are delivered without mounting plate
Note 2	An external additional supply (AUX POWER) of 20 to 30 V DC is required for the supply of the output circuits. The additional supply must comply with VDE 0106 (PELV), protection class III.

Sensor supply

type of voltage supply for power supply	using AS-Interface
input voltage	20 ... 30 V
property of the sensor supply short-circuit and overload resistant	Yes
ampacity of the sensor supply for all inputs	
• at ambient temperature 40 °C	200 mA

Inputs

number of digital inputs	4
type of connection technology	2- and 3-wire technology
Input circuit	PNP transistor
type of voltage of the input voltages	DC
Inputs switching level High min	10 V
input current at digital input	
• for signal <1> minimum	6 mA
• with signal <0> maximum	1.5 mA
Inputs	
• sensor supply using AS-Interface	short-circuit and overload resistant
• socket assignment	
— PIN 1	sensor supply L+
— PIN 2	data input II
— PIN 3	sensor supply L-
— PIN 4	data input I

— PIN 5		ground terminal	
design of the pin assignment of the inputs		Y-II assignement	
Outputs			
number of digital outputs		3	
type of voltage of output voltages		DC	
Outputs external power supply 24 V DC		using black AS-Interface flat cable	
ampacity of the semiconductor output at DC-13 at 24 V		2 A	
Outputs aggregate current max		4 A	
type of switching output		PNP transistor	
design of the pin assignment of the outputs		Y-II assignement	
Outputs socket assignment		3 = "-", 2/4 = output, 5 = ground terminal	
property of the output short-circuit proof		Yes	
Outputs			
• short-ciruit protection		built-in	
• induction protection		built-in	
• watchdog		built-in	
Assignment of the data bits			
Assignment of data bits			
• socket		PIN 4 = IN1 (D0), PIN 2 = IN2 (D1)	
• socket 2		PIN 4 = IN2 (D1)	
• socket 3		PIN 4 = IN3 (D2) , PIN 2 = IN4 (D3)	
• socket 4		PIN 4 = IN4 (D3)	
• socket 5		PIN4 = OUT1 (D0), PIN2 = OUT2 (D1)	
• socket 6		PIN4 = OUT2 (D1)	
• socket 7		PIN4 = OUT3 (D2)	
• socket 8		not assigned (closed)	
Ambient conditions			
ambient temperature			
• during operation		-25 ... +85 °C	
• during storage		-40 ... +85 °C	
protection class IP		IP67	
Display			
Status display			
• display of I/Os		yellow LED	
• display of Uaux		green LED	
• display of AS-Interface/diagnostics		green/red LED	
Mechanical data			
width		60 mm	
height		152 mm	
depth		29 mm	
fastening method		standard rail mounting/wall mounting using mounting plate for K60 compact module	
shock resistance		15g / 11 ms	
Certificates/ approvals			
General Product Approval		EMC	Declaration of Conformity



[Confirmation](#)



Marine / Shipping

other



Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK2400-1FQ03-0AA3>


Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK2400-1FQ03-0AA3>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK2400-1FQ03-0AA3>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK2400-1FQ03-0AA3&lang=en

last modified:

3/10/2021