

SIEMENS

Product data sheet

3RT1046-1AV00


Abb. ähnlich / similar picture

 CONTACTOR, AC-3 45 KW/400 V, AC 400 V,
50 HZ, 3-POLE, SIZE S3, SCREW CONNECTION

General details:

Size of the contactor	S3
Number of poles	3

Control circuit:

Design of activation of the operating mechanism	conventional
---	--------------

Type of voltage	AC
-----------------	----


Control supply voltage	
• at 50 Hz / for AC / rated value / minimum	400 V
• at 50 Hz / for AC / rated value / maximum	400 V

Supply voltage frequency / for auxiliary and control current circuit / rated value	
• minimum	50 Hz
• maximum	50 Hz

Main circuit:

Number of NC contacts / for main contacts	0
Number of NO contacts / for main contacts	3
Operating current	
• at AC-3 / at 400 V / rated value	95 A
• at AC-1 / at 400 V / rated value	120 A

Service power	
• at AC-3 / at 400 V / rated value	45 kW
• at AC-1 / at 400 V / rated value	66 kW
Auxiliary circuit:	
Number of NO contacts / for auxiliary contact	0
Number of NC contacts / for auxiliary contact	0
Connection type:	
Design of the electrical connection / for main current circuit	screw-type terminals
Design of the electrical connection / for auxiliary and control current circuit	screw-type terminals
Mounting/fixing:	
Type of fixing/fixation	screw and snap-on mounting onto 35 mm and 75 mm standard mounting rail
Series installation	Yes



last change:

10/31/2006

Technical Assistance:	Telephone:	+49 (0) 911-895-5900 (8°° - 17°° CET)
	Fax:	+49 (0) 911-895-5907
	E-Mail:	technical-assistance@siemens.com
	Internet:	www.siemens.de/lowvoltage/technical-assistance