



Surge suppressor, diode combination, 12 ... 250 V DC, for contactor relays and motor contactors Size S00

General technical data			
product brand name		SIRIUS	
product designation		surge suppressor	
size of contactor		S00	
design of the surge suppressor		Diode combination	
ambient temperature			
• during storage	°C	-40 ... +80	
• during operation	°C	-25 ... +60	
Control circuit/ Control			
type of voltage of the control supply voltage		DC	
control supply voltage 1			
• at DC	V	12 ... 250	
Installation/ mounting/ dimensions			
mounting position		any	
fastening method		clip-on	
width	mm	28	
height	mm	46	
depth	mm	9	
Certificates/ approvals			
certificate of suitability		CE / UL / CSA	
General Product Approval		EMC	Declaration of Conformity



[Confirmation](#)



Declaration of Conformity	Test Certificates		Marine / Shipping		
 EG-Konf.	Special Test Certificate	Type Test Certificates/Test Report	 BUREAU VERITAS	 DNV	 PRS
Marine / Shipping		other	Railway		



[Environmental Con-
firmations](#)

[Confirmation](#)



[Vibration and Shock](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2916-1EH00>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2916-1EH00>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2916-1EH00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2916-1EH00&lang=en





last modified:

10/22/2022 