



Magnet coil for contactors 18.5 kW 600 V AC, 60Hz, for motor contactors, Size S0, Screw terminal

**General technical data**

product brand name	SIRIUS
product designation	Magnet coil

**Control circuit**

type of voltage of the control supply voltage	AC
power loss [V·A] of magnet coil at AC typical control supply voltage	9.8 VA
<ul style="list-style-type: none"> <li>1 at AC           <ul style="list-style-type: none"> <li>— at 50 Hz rated value</li> </ul> </li> </ul>	660 V
operating range factor control supply voltage rated value of magnet coil at AC	
<ul style="list-style-type: none"> <li>at 50 Hz</li> <li>at 60 Hz</li> </ul>	0.8 ... 1.1 0.85 ... 1.1

**Certificates/ approvals**

General Product Approval	EMC	Declaration of Conformity	Marine / Shipping
--------------------------	-----	---------------------------	-------------------

[Confirmation](#)



Marine / Shipping	other
-------------------	-------



[Confirmation](#)

[Environmental Confirmations](#)



**Further information**

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2926-5AT61>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2926-5AT61>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2926-5AT61>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2926-5AT61&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2926-5AT61&lang=en)

last modified:

1/18/2021 