

OVERLOAD RELAY, 7...10 A, 1NO+1NC, SIZE S0, CLASS 10,  
MAIN CIRCUIT: SCREW CONNECTION, AUXILIARY CIRCUIT:  
CAGE CLAMP, FOR CONTACTOR MOUNTING



Figure similar

|                                                           |                        |
|-----------------------------------------------------------|------------------------|
| product brand name                                        | SIRIUS                 |
| Product designation                                       | thermal overload relay |
| General technical data:                                   |                        |
| Size of overload relay                                    | S0                     |
| Size of contactor can be combined company-specific        | S0                     |
| Power loss [W] total typical                              | 6 W                    |
| Insulation voltage with degree of pollution 3 rated value | 690 V                  |
| Surge voltage resistance rated value                      | 6 kV                   |
| Protection class IP                                       | IP20                   |
| • on the front                                            |                        |
| Shock resistance                                          | 8g / 10 ms             |
| Type of protection                                        | DMT 98 ATEX G 001      |
| Protection against electrical shock                       | finger-safe            |
| Equipment marking acc. to DIN EN 81346-2                  | F                      |
| Ambient conditions:                                       |                        |
| Installation altitude at height above sea level maximum   | 2 000 m                |
| Ambient temperature                                       |                        |

|                                           |                |
|-------------------------------------------|----------------|
| • during operation                        | -20 ... +70 °C |
| • during storage                          | -55 ... +80 °C |
| • during transport                        | -55 ... +80 °C |
| <b>Relative humidity during operation</b> | 100 %          |

#### Main circuit:

|                                                                                   |            |
|-----------------------------------------------------------------------------------|------------|
| <b>Number of poles for main current circuit</b>                                   | 3          |
| <b>Adjustable pick-up value current of the current-dependent overload release</b> | 7 ... 10 A |
| <b>Operating voltage</b>                                                          |            |
| • at AC-3 rated value maximum                                                     | 690 V      |

#### Auxiliary circuit:

|                                                         |        |
|---------------------------------------------------------|--------|
| <b>Number of NC contacts</b>                            |        |
| • for auxiliary contacts                                | 1      |
| <b>Number of NO contacts</b>                            |        |
| • for auxiliary contacts                                | 1      |
| <b>Number of CO contacts</b>                            |        |
| • for auxiliary contacts                                | 0      |
| <b>Operating current of auxiliary contacts at AC-15</b> |        |
| • at 24 V                                               | 3 A    |
| • at 110 V                                              | 3 A    |
| • at 120 V                                              | 3 A    |
| • at 125 V                                              | 3 A    |
| • at 230 V                                              | 2 A    |
| • at 400 V                                              | 1 A    |
| <b>Operating current of auxiliary contacts at DC-13</b> |        |
| • at 24 V                                               | 1 A    |
| • at 110 V                                              | 0.22 A |
| • at 125 V                                              | 0.22 A |
| • at 220 V                                              | 0.11 A |

#### Protective and monitoring functions:

|                   |          |
|-------------------|----------|
| <b>Trip class</b> | Class 10 |
|-------------------|----------|

#### Short-circuit protection

|                                                                 |                              |
|-----------------------------------------------------------------|------------------------------|
| <b>Design of the fuse link</b>                                  |                              |
| • for short-circuit protection of the auxiliary switch required | fuse gL/gG: 6 A, quick: 10 A |

#### Installation/ mounting/ dimensions:

|                          |                                                                                                                         |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------|
| <b>Mounting position</b> | with vertical mounting surface +/-135° rotatable, with vertical mounting surface +/- 45° tiltable to the front and back |
| <b>Mounting type</b>     | direct mounting                                                                                                         |
| <b>Height</b>            | 97 mm                                                                                                                   |
| <b>Width</b>             | 45 mm                                                                                                                   |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |       |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|
| <b>Depth</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 96 mm |
| <b>Required spacing</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |       |
| <ul style="list-style-type: none"> <li>• with side-by-side mounting <ul style="list-style-type: none"> <li>— forwards 0 mm</li> <li>— Backwards 0 mm</li> <li>— upwards 0 mm</li> <li>— downwards 0 mm</li> <li>— at the side 0 mm</li> </ul> </li> <li>• for grounded parts <ul style="list-style-type: none"> <li>— forwards 0 mm</li> <li>— Backwards 0 mm</li> <li>— upwards 0 mm</li> <li>— at the side 6 mm</li> <li>— downwards 0 mm</li> </ul> </li> <li>• for live parts <ul style="list-style-type: none"> <li>— forwards 0 mm</li> <li>— Backwards 0 mm</li> <li>— upwards 0 mm</li> <li>— downwards 0 mm</li> <li>— at the side 6 mm</li> </ul> </li> </ul> |       |

#### Connections/ Terminals:

|                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                              |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|
| <b>Product function</b>                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                              |
| <ul style="list-style-type: none"> <li>• removable terminal for auxiliary and control circuit</li> </ul>                                                                                                                                                                                                                                                                                                                                                  | No                                           |
| <b>Type of electrical connection</b>                                                                                                                                                                                                                                                                                                                                                                                                                      |                                              |
| <ul style="list-style-type: none"> <li>• for main current circuit</li> <li>• for auxiliary and control current circuit</li> </ul>                                                                                                                                                                                                                                                                                                                         | screw-type terminals<br>Cage Clamp terminals |
| <b>Type of connectable conductor cross-sections</b>                                                                                                                                                                                                                                                                                                                                                                                                       |                                              |
| <ul style="list-style-type: none"> <li>• for main contacts <ul style="list-style-type: none"> <li>— solid 2 x (1 ... 2.5 mm<sup>2</sup>), 2 x (2.5 ... 6 mm<sup>2</sup>), max. 2 x (2.5 ... 10 mm<sup>2</sup>)</li> <li>— finely stranded with core end processing 2x (1 ... 2.5 mm<sup>2</sup>), 2x (2.5 ... 6 mm<sup>2</sup>), 1x 10 mm<sup>2</sup></li> </ul> </li> <li>• at AWG conductors for main contacts 2x (16 ... 12), 2x (14 ... 8)</li> </ul> |                                              |
| <b>Type of connectable conductor cross-sections</b>                                                                                                                                                                                                                                                                                                                                                                                                       |                                              |
| <ul style="list-style-type: none"> <li>• for auxiliary contacts <ul style="list-style-type: none"> <li>— solid 2x (0.5 ... 2.5 mm<sup>2</sup>)</li> <li>— finely stranded with core end processing 2x (0.5 ... 1.5 mm<sup>2</sup>)</li> <li>— finely stranded without core end processing 2x (0.5 ... 1.5 mm<sup>2</sup>)</li> </ul> </li> <li>• at AWG conductors for auxiliary contacts 2x (20 ... 14)</li> </ul>                                       |                                              |

#### Certificates/approvals

| General Product Approval | For use in hazardous locations |
|--------------------------|--------------------------------|
|--------------------------|--------------------------------|



| Declaration of Conformity | Test Certificates | Shipping Approval |
|---------------------------|-------------------|-------------------|
|---------------------------|-------------------|-------------------|



[spezielle  
Prüfbescheinigunge  
n](#)

[Typprüfbescheinigu  
ng/Werkszeugnis](#)



| Shipping Approval | other |
|-------------------|-------|
|-------------------|-------|



[Umweltbestätigung](#)

[sonstig](#)

| Railway |
|---------|
|---------|

[Bestätigungen](#)

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RU11261JD0>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RU11261JD0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<https://support.industry.siemens.com/cs/ww/en/ps/3RU11261JD0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RU11261JD0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RU11261JD0&lang=en)



MEBERSCHREIZAIS FUER



QUOTRIEOPABORIELAYONOR