



Circuit breaker size S2 for motor protection, Class 10 A-release 28...40 A
Short-circuit release 520 A Screw terminal Standard switching capacity !!!
Phased-out product !!! Successor is SIRIUS 3RV2 Preferred successor
type is >>3RV2031-4UA10<<

product brand name	SIRIUS
product designation	circuit breaker
design of the product	for motor protection

General technical data

product extension auxiliary switch	Yes
power loss [W] for rated value of the current	
• at AC in hot operating state	29 W
• at AC in hot operating state per pole	9.7 W
surge voltage resistance rated value	6 000 V
protection class IP on the front	IP20
shock resistance	25g / 11 ms
mechanical service life (switching cycles) of the main contacts typical	50 000
continuous current rated value	40 A
Substance Prohibitance (Date)	07/01/2006

Ambient conditions

installation altitude at height above sea level maximum	2 000 m
ambient temperature	
• during operation	-20 ... +60 °C
• during storage	-50 ... +80 °C
• during transport	-50 ... +80 °C

Main circuit

number of poles for main current circuit	3
adjustable current response value current of the current-dependent overload release	28 ... 40 A
operating voltage	
• rated value	690 V
• at AC-3 rated value maximum	690 V
operational current at AC-3 at 400 V rated value	40 A
operating power at AC-3	
• at 400 V rated value	18.5 kW
operating frequency at AC-3 maximum	15 1/h

Auxiliary circuit

number of CO contacts for auxiliary contacts	0
--	---

Protective and monitoring functions

product function	
• ground fault detection	No
• phase failure detection	Yes
trip class	CLASS 10
breaking capacity maximum short-circuit current (Icu)	
• at AC at 240 V rated value	100 kA

- at AC at 400 V rated value
- at AC at 500 V rated value
- at AC at 690 V rated value

50 kA
10 kA
4 kA

Short-circuit protection

design of the overcurrent release and short-circuit release

thermomagnetic

Installation/ mounting/ dimensions

mounting position

any

fastening method

screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 50022

height

140 mm

width

55 mm

depth

149 mm

required spacing with side-by-side mounting

- backwards
- at the side

0 mm
0 mm

Connections/ Terminals

product component removable terminal for auxiliary and control circuit

No

type of electrical connection

- for main current circuit
- for auxiliary and control circuit

screw-type terminals with box terminals
screw-type terminals
front side

arrangement of electrical connectors for main current circuit

type of connectable conductor cross-sections

- for main contacts
 - solid
 - stranded
 - finely stranded with core end processing
- at AWG cables for main contacts

2x (0.75 ... 16 mm²)
2x (0.75 ... 25 mm²), 1x (0.75 ... 35 mm²)
2x (0.75 ... 16 mm²), 0.75 ... 25 mm²
2x (18 ... 2), 1x (18 ... 2)

Safety related data

touch protection against electrical shock

finger-safe

Certificates/ approvals

General Product Approval

For use in hazard-
ous locations



[Confirmation](#)



For use in hazard-
ous locations

Declaration of Conformity

Test Certificates

Marine / Shipping



[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)



Marine / Shipping

other



[Miscellaneous](#)

[Confirmation](#)



Railway

[Special Test Certificate](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RV1031-4FA10>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RV1031-4FA10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RV1031-4FA10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)


http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RV1031-4FA10&lang=en


Characteristic: Tripping characteristics, I²t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RV1031-4FA10/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RV1031-4FA10&objecttype=14&gridview=view1>





last modified:

11/21/2022 [↗](#)