SIEMENS

Data sheet 3RX9015-0AA00

AS-i cable, shaped yellow, pure, oil-resistant $2x\,1.5$ mm2, 100 m consists of 100 m cable Shipbuilding approval



00		
-30	-30 +80 °C	
-40	-40 +80 °C	
resis	resistant	
resis	resistant	
flam	flame-retardant according to IEC 60332-1;VDE 0482 T. 265-2-1	
brov	brown, blue	
N VDE 0472 no b	no break after 30000 reverse bending cycles	
good	good	
yes	yes	
24 n	24 mm	
issible 12 n	12 mm	
yes	yes	
100	100 m roll	
PUF	PUR	
yello	yellow (AS-Interface)	
AS-	AS-Interface shaped cables	
	yello PUF 100 yes issible 12 n 24 n yes good N VDE 0472 no b brov flam resis resis	PUR 100 m roll yes 12 mm 24 mm yes good no break after 30000 reverse b brown, blue flame-retardant according to IE resistant resistant

Confirmation



CE



Confirmation

Further information

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RX9015-0AA00

Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RX9015-0AA00
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RX9015-0AA00
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RX9015-0AA00&lang=en

last modified: 12/16/2022 🖸