



LAMPHOLDER W2 X 4.6D, WITHOUT LAMP,
WITH HOLDER

Mechanical design:

product designation		lampholder
Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		0
Number of change-over switches / for auxiliary contacts		0
Number of lampholders		1
Execution of the mounting		W2 x 4.6d
Product component / fluorescent materials		No
Design of the electrical connection		tab terminals

General technical details:

Type of voltage / of the operating voltage		AC/DC
Operating voltage		
• at 50 Hz / at AC		
• rated value	V	5 ... 60
• at 60 Hz / at AC		
• rated value	V	5 ... 60
• for DC		
• rated value	V	5 ... 60
Operating current		
• at AC-15 / at 230 V		

• at 50 Hz / rated value	A	4
• at DC-13 / at 24 V / rated value	A	3
Resistance against shock / for devices with incandescent lamp / according to IEC 60068-2-27		<= 30g
Resistance against vibration / according to IEC 60068-2-6		20 ... 200 Hz: 5g
Item designation / according to DIN EN 61346-2		P
Item designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		H
Ambient temperature		
• during operating	°C	-25 ... +60
• during storage	°C	-40 ... +80
Protection class IP / of the terminal		IP00
protection class IP / of the housing		IP00
Type of mounting		front mounting
Width	mm	19
Height	mm	19
Depth	mm	46

Certificates/approvals:

General Product Approval

other



CCC



CSA



GOST



UL

[Confirmation](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator:

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3SB2304-2A/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SB2304-2A

last change:

Feb 7, 2012