SIEMENS

Data sheet

3SB3000-0DA41



22MM PLASTIC ROUND ACTUATOR: PUSHBUTTON LATCHING, UNLOCKING BY PRESSING AGAIN WITH FLAT BUTTON WITH HOLDER GREEN !!! Phasedout product !!! SIRIUS ACT 3SU1 is successor Preferred successor type is >>3SU1000-0AA40-0AA0 + 3SU1500-0AA10-0AA0<<

de store of the survey of the	Qia alla das ina assurad
design of the product	Single device round
Enclosure	
number of command points	1
Actuator	
design of the actuating element	push button
principle of operation of the actuating element	latching
product extension optional light source	No
color of the actuating element	green
material of the actuating element	plastic
shape of the actuating element	Flat pushbutton
outer diameter of the actuating element	28.5 mm
type of unlocking device	push-to-unlatch mechanism
number of switching positions	2
Front ring	
product component front ring	Yes
design of the front ring	Standard
material of the front ring	plastic
color of the front ring	black
Holder	
material of the holder	Plastic
General technical data	
product function	
 EMERGENCY OFF function 	No
 EMERGENCY STOP function 	No
protection class IP	IP66
vibration resistance according to IEC 60068-2-6	20 200 Hz: 5g
operating frequency maximum	1 000 1/h
mechanical service life (operating cycles) typical	300 000
reference code according to IEC 81346-2	S
Substance Prohibitance (Date)	07/01/2006
Connections/ Terminals	
tightening torque of the screws in the bracket	1 1.2 N·m
Ambient conditions	
ambient temperature	
 during operation 	-25 +70 °C
during storage	-40 +80 °C
environmental category during operation according to IEC 60721	3К6
Installation/ mounting/ dimensions	

fastening method		fron	t mounting				
shape of the installation openi	ng	rour	round				
mounting diameter		22 r	22 mm				
mounting height		8 m	8 mm				
installation width		28.5	28.5 mm				
installation depth		29 r	29 mm				
ertificates/ approvals							
General Product Approval			Marine / Shipping				
SP SM	ų, "	EAC	Lloyd's Register Lirs	PRS	RINA		
Marine / Shipping other							
	onfirmation	<u>Miscellaneous</u>					
urther information Siemens has decided to exit th https://press.siemens.com/globa Siemens is working on the ren Please contact your local Sieme	I/en/pressrelease ewal of the curr	e/siemens-wind-down-ru rent EAC certificates.		to import or offer to sup	nly these products to an		
EAC relevant market (other than					ply these products to all		
Information on the packaging			·				
https://support.industry.siemens. Information- and Downloadcer							
https://www.siemens.com/ic10	itel (Catalogs, E	siocitures,)					
Industry Mall (Online ordering							
	n/mall/en/en/Cata	alog/product?mlfb=3SB3	<u>3000-0DA41</u>				
Cax online generator	s com/WW/CAX	order/default aspx?lang	en&mlfb=3SB3000-0DA41				
Cax online generator http://support.automation.siemer			en&mlfb=3SB3000-0DA41				
http://support.automation.siemer Service&Support (Manuals, Ce https://support.industry.siemens.	ertificates, Chara com/cs/ww/en/ps	acteristics, FAQs,) s/3SB3000-0DA41					
Cax online generator http://support.automation.siemer Service&Support (Manuals, Ce	ertificates, Chara com/cs/ww/en/ps jes, 2D dimensio	acteristics, FAQs,) <u>s/3SB3000-0DA41</u> on drawings, 3D model	s, device circuit diagrams				

last modified:

1/18/2021 🖸