# **SIEMENS**

Product data sheet 3SB3000-2KA11

22MM PLASTIC ROUND ACTUATOR: SELECTOR SWITCH 2 SWITCH POSITIONS O-I LATCHING NON-ILLUMINATED WITH HOLDER BLACK

Actuator / signaling device:			
Design of the operating mechanism		selector switch	
Type of unlocking device		rotate-to-unlatch mechanism	
Color / of the activation element		black	
Material / of the activation element		plastic	
Number of switching positions		2	
Actuating angle			
• clockwise	٥	50	
Product component / front ring		Yes	
Material / of the front ring		plastic	
Color / of the front ring		black	
Design of front ring		Standard	
Product function / EMERGENCY STOP function		No	
Holder:			
Material / of holder		Plastic	
General technical details:			
General technical details:  Resistance against shock			
		<= 50g	
Resistance against shock  • for devices without incandescent lamp / according to IEC 60068-		<= 50g 20 200 Hz: 5g	
Resistance against shock  • for devices without incandescent lamp / according to IEC 60068-2-27	1/h		
Resistance against shock  • for devices without incandescent lamp / according to IEC 60068-2-27  Resistance against vibration / according to IEC 60068-2-6	1/h	20 200 Hz: 5g	
Resistance against shock  • for devices without incandescent lamp / according to IEC 60068-2-27  Resistance against vibration / according to IEC 60068-2-6  Operating cycles / maximum	1/h	20 200 Hz: 5g 1,000	
Resistance against shock  • for devices without incandescent lamp / according to IEC 60068-2-27  Resistance against vibration / according to IEC 60068-2-6  Operating cycles / maximum  Mechanical operating cycles as operating time / typical	1/h	20 200 Hz: 5g 1,000	
Resistance against shock  • for devices without incandescent lamp / according to IEC 60068-2-27  Resistance against vibration / according to IEC 60068-2-6  Operating cycles / maximum  Mechanical operating cycles as operating time / typical  Item designation	1/h	20 200 Hz: 5g 1,000 300,000	
Resistance against shock  • for devices without incandescent lamp / according to IEC 60068-2-27  Resistance against vibration / according to IEC 60068-2-6  Operating cycles / maximum  Mechanical operating cycles as operating time / typical  Item designation  • according to DIN EN 61346-2  • according to DIN 40719 extendable after IEC 204-2 / according	1/h N·m	20 200 Hz: 5g 1,000 300,000	
Resistance against shock  • for devices without incandescent lamp / according to IEC 60068-2-27  Resistance against vibration / according to IEC 60068-2-6  Operating cycles / maximum  Mechanical operating cycles as operating time / typical  Item designation  • according to DIN EN 61346-2  • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		20 200 Hz: 5g 1,000 300,000 S S	
Resistance against shock  • for devices without incandescent lamp / according to IEC 60068-2-27  Resistance against vibration / according to IEC 60068-2-6  Operating cycles / maximum  Mechanical operating cycles as operating time / typical  Item designation  • according to DIN EN 61346-2  • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750  Tightening torque / of the screws in the bracket / maximum		20 200 Hz: 5g 1,000 300,000 S S	
Resistance against shock  • for devices without incandescent lamp / according to IEC 60068-2-27  Resistance against vibration / according to IEC 60068-2-6  Operating cycles / maximum  Mechanical operating cycles as operating time / typical  Item designation  • according to DIN EN 61346-2  • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750  Tightening torque / of the screws in the bracket / maximum  Ambient temperature	N∙m	20 200 Hz: 5g 1,000 300,000 S S	

climatic class / during the operating phase / according to EN 60721		3K6
Type of mounting		front mounting
Shape / of the installation hole		round
Installation width	mm	28.5
Mounting diameter	mm	22
Mounting height	mm	24
Mounting depth	mm	29

## Certificates/approvals:

#### **General Product Approval**





Test Certificates

Special Test Certificate

## **Shipping Approval**













#### other

Confirmation

other



### **Further information:**

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/industrial-controls/mall

Cax online generator:


http://www.siemens.com/cax

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/3SB3000-2KA11/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=3SB3000-2KA11



last change: Jul 17, 2012