



Enclosure for command devices, 22 mm, round, Enclosure material metal, Enclosure top part yellow, with protective collar, 1 control point metal, A=EMERGENCY STOP mushroom pushbutton red, 40 mm, rotate-to-unlatch, 1 NC, 1 NC, screw terminal, floor mounting, 1xM20 each on top and bottom

product brand name
product designation
product type designation
equipment of commanding and signaling device

manufacturer's article number

- of supplied contact module
- of supplied contact module at the command point A 1
- of supplied contact module at the command point A 2
- of the supplied holder
- of the supplied holder at the command point A
- of the supplied actuator
- of the supplied actuator at the command point A
- of supplied empty enclosure

SIRIUS ACT

Enclosures

3SU1

A = EMERGENCY STOP mushroom pushbutton, 40 mm, with positive latching acc. to ISO 13850 and rotate-to-unlatch mechanism

A1 = 3SU1400-2AA10-1CA0, A2 = 3SU1400-2AA10-1CA0

[3SU1400-2AA10-1CA0](#)

[3SU1400-2AA10-1CA0](#)

A = 3SU1550-0AA10-0AA0

[3SU1550-0AA10-0AA0](#)

A = 3SU1050-1HB20-0AA0

[3SU1050-1HB20-0AA0](#)

[3SU1851-0AA00-0AC2](#)

Enclosure

design of the housing

shape of the enclosure front

material of the enclosure

number of command points

product component

- EMERGENCY STOP device
- protective collar

color of the enclosure top part

delivery state

- as a kit
- pre-wired on strip terminal

fastening method of the enclosure

with protective collar

Square

metal

1

Yes

No

yellow

No

No

Vertical

Actuator

design of the actuating element

suitability for use EMERGENCY OFF switch

product feature lockout

product extension optional light source

color of the actuating element

material of the actuating element

shape of the actuating element

number of contact modules

type of unlocking device

EMERGENCY STOP mushroom pushbutton

Yes

No

No

red

plastic

round

2

A = rotate-to-unlatch mechanism

Front ring

product component front ring

design of the front ring

No

Standard

Holder	
material of the holder	Plastic
Display	
number of LED modules	0
General technical data	
product function	Yes
• positive opening	Yes
• EMERGENCY OFF function	Yes
• EMERGENCY STOP function	Yes
protection class IP	IP66, IP67, IP69(IP69K)
degree of protection NEMA rating	1, 2, 3, 3R, 4, 4X, 12, 13
shock resistance	
• according to IEC 60068-2-27	sinusoidal half-wave 15g / 11 ms
vibration resistance	
• according to IEC 60068-2-6	10 ... 500 Hz: 5g
reference code according to IEC 81346-2	S
continuous current of the C characteristic MCB	10 A; for a short-circuit current smaller than 400 A
continuous current of the quick DIAZED fuse link	10 A
continuous current of the DIAZED fuse link gG	10 A
Substance Prohibitance (Date)	10/01/2014
operating voltage	
• at AC	
— at 50 Hz rated value	5 ... 500 V
— at 60 Hz rated value	5 ... 500 V
• at DC rated value	5 ... 500 V
Communication/ Protocol	
design of the interface for communication	without
Auxiliary circuit	
design of the contact of auxiliary contacts	Silver alloy
number of NC contacts for auxiliary contacts	2
number of NO contacts for auxiliary contacts	0
Connections/ Terminals	
type of electrical connection of modules and accessories	Screw-type terminal
type of electrical connection on enclosure	Cable routing above and below, both 1 x M20
tightening torque of the screws in the bracket	1 ... 1.2 N·m
tightening torque of fixing screws in the enclosure cover	1.5 ... 1.7 N·m
tightening torque with screw-type terminals	0.8 ... 0.9 N·m
Ambient conditions	
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
environmental category during operation according to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%, no condensation in operation permitted for all devices behind front panel)
Installation/ mounting/ dimensions	
fastening method of modules and accessories	Floor mounting
height	89.4 mm
width	85 mm
depth	112.5 mm
shape of the installation opening	round
Accessories	
number of labels	0
number of inscription plates	0
Certificates/ approvals	
General Product Approval	



[Confirmation](#)



Declaration of Conformity	Test Certificates	Marine / Shipping
---------------------------	-------------------	-------------------



[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)



Marine / Shipping	other
-------------------	-------



[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1851-0NB00-2AC2>

Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1851-0NB00-2AC2>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1851-0NB00-2AC2>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1851-0NB00-2AC2&lang=en





last modified:

1/26/2022 