




pushbutton, flat, blue, for pushbutton

|                                                                |                                                                    |
|----------------------------------------------------------------|--------------------------------------------------------------------|
| product brand name                                             | SIRIUS ACT                                                         |
| product designation                                            | Button                                                             |
| design of the product                                          | flat                                                               |
| product type designation                                       | 3SU1                                                               |
| Actuator                                                       |                                                                    |
| outer diameter of the actuating element                        | 23.7 mm                                                            |
| Substance Prohibitance (Date)                                  | 10/01/2014                                                         |
| Ambient conditions                                             |                                                                    |
| ambient temperature                                            |                                                                    |
| • during operation                                             | 70 ... -25 °C                                                      |
| • during storage and transport                                 | -40 ... +80 °C                                                     |
| environmental category during operation according to IEC 60721 | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%) |
| Installation/ mounting/ dimensions                             |                                                                    |
| depth                                                          | 2.2 mm                                                             |
| Accessories                                                    |                                                                    |
| material of accessory                                          | Plastic                                                            |
| color of accessory                                             | blue                                                               |
| Certificates/ approvals                                        |                                                                    |
| General Product Approval                                       | Declaration of Conformity                                          |



[Confirmation](#)



|                   |                   |
|-------------------|-------------------|
| Test Certificates | Marine / Shipping |
|-------------------|-------------------|

[Type Test Certificates/Test Report](#)



|       |
|-------|
| other |
|-------|

[Environmental Confirmations](#)

[Confirmation](#)

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1900-0FT50-0AA0>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1900-0FT50-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1900-0FT50-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1900-0FT50-0AA0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1900-0FT50-0AA0&lang=en)



last modified:

4/4/2022 