

Contactor relay, 71E, EN 50011, 7 NO + 1 NC; Screw terminal Width 45 mm 24 V DC DC operation !!! Phased-out product !!! Successor is SIRIUS 3RH21

product designation	Auxiliary contactor
product type designation	3TH2
size of contactor	0
reference code according to IEC 81346-2	K
Substance Prohibitance (Date)	07/01/2006
ambient temperature during operation	-25 ... +55 °C
type of voltage of the control supply voltage	DC
control supply voltage at DC	
• rated value	24 V
number of NC contacts for auxiliary contacts	1
• delayed switching	0
• lagging switching	0
• make-before-break switching	0
number of NO contacts for auxiliary contacts	7
• delayed switching	0
• leading contact	0
• make-before-break switching	0
number of CO contacts for auxiliary contacts	0
identification number and letter for switching elements	71 E
operational current at AC-15	
• at 230 V rated value	4 A
• at 400 V rated value	3 A
fastening method	screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 50022
height	48 mm
width	45 mm
depth	96 mm
type of electrical connection for auxiliary and control circuit	screw-type terminals

Safety related data

B10 value with high demand rate according to SN 31920	400 000; With 0.3 x I _e
T1 value for proof test interval or service life according to IEC 61508	20 y

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TH2271-0BB4>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TH2271-0BB4>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TH2271-0BB4>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TH2271-0BB4&lang=en

Characteristic: Tripping characteristics, I_t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3TH2271-0BB4/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3TH2271-0BB4&objecttype=14&gridview=view1>

last modified:

11/21/2022 