



Figure similar

Miniature contactor, Flat connector terminal 2 NO + 2 NC Screw mounting (diagonal) 24 VDC DC operation !!! Phased-out product !!! Successor is SIRIUS 3RT23/25

**product designation**

**product type designation**

**size of contactor**

protection class IP on the front

**reference code according to IEC 81346-2**

**Substance Prohibitance (Date)**

ambient temperature during operation

**number of poles for main current circuit**

**number of NO contacts for main contacts**

**number of NC contacts for main contacts**

**operational current**

- at AC-1 at 400 V
  - at ambient temperature 40 °C rated value
- at AC-3 at 400 V rated value

**operating power**

- at AC-1 at 400 V rated value
- at AC-3 at 400 V rated value

**type of voltage of the control supply voltage**

**control supply voltage at DC**

- rated value

**control version of the switch operating mechanism**

**number of NC contacts for auxiliary contacts**

- instantaneous contact
- lagging switching

number of NO contacts for auxiliary contacts

- instantaneous contact
- leading contact

**fastening method**

- side-by-side mounting

**height**

**width**

**depth**

**type of electrical connection**

- for main current circuit
- for auxiliary and control circuit

Miniature contactor

3TK20

0

IP00

Q

07/01/2006

-25 ... +55 °C

4

2

2

16 A

9 A

10 kW

4 kW

DC

24 V

conventional

0

0

0

0

0

screw fixing

Yes

36 mm

45 mm

60 mm

tab terminals 6,3 mm

tab terminals 6.3 mm

**Further information**

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

**Information on the packaging**

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TK2022-7BB4>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TK2022-7BB4>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3TK2022-7BB4>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3TK2022-7BB4&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TK2022-7BB4&lang=en)

**Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current**

<https://support.industry.siemens.com/cs/ww/en/ps/3TK2022-7BB4/char>

**Further characteristics (e.g. electrical endurance, switching frequency)**

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3TK2022-7BB4&objecttype=14&gridview=view1>

last modified:

1/18/2021 