



Figure similar

Miniature contactor, Flat connector terminal, 4 NO Snap-on mounting standard mounting rail 220 V AC 50/60 Hz AC operation !!! Phased-out product !!! Successor is SIRIUS 3RT23/25

<b>product designation</b>	Miniature contactor
<b>product type designation</b>	3TK20
<b>size of contactor</b>	0
protection class IP on the front	IP00
<b>reference code according to IEC 81346-2</b>	Q
<b>Substance Prohibitance (Date)</b>	07/01/2006
ambient temperature during operation	-25 ... +55 °C
<b>number of poles for main current circuit</b>	4
<b>number of NO contacts for main contacts</b>	4
<b>number of NC contacts for main contacts</b>	0
<b>operational current</b>	
• at AC-1 at 400 V	16 A
— at ambient temperature 40 °C rated value	9 A
• at AC-3 at 400 V rated value	
<b>operating power</b>	
• at AC-1 at 400 V rated value	10 kW
• at AC-3 at 400 V rated value	4 kW
<b>type of voltage of the control supply voltage</b>	AC
<b>control supply voltage at AC</b>	
• at 50 Hz rated value	220 V
• at 60 Hz rated value	220 V
<b>control supply voltage frequency</b>	
• 1 rated value	50 Hz
• 2 rated value	60 Hz
<b>control version of the switch operating mechanism</b>	conventional
<b>number of NC contacts for auxiliary contacts</b>	0
• instantaneous contact	0
• lagging switching	0
<b>number of NO contacts for auxiliary contacts</b>	0
• instantaneous contact	0
• leading contact	0
<b>fastening method</b>	screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 50022
• side-by-side mounting	Yes
<b>height</b>	48 mm
<b>width</b>	45 mm
<b>depth</b>	64.5 mm
<b>type of electrical connection</b>	
• for main current circuit	tab terminals 6,3 mm
• for auxiliary and control circuit	tab terminals 6.3 mm

Further information

**Siemens has decided to exit the Russian market (see here).**

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

**Siemens is working on the renewal of the current EAC certificates.**

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

**Information on the packaging**

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TK2040-3AN2>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TK2040-3AN2>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3TK2040-3AN2>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3TK2040-3AN2&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TK2040-3AN2&lang=en)

**Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current**

<https://support.industry.siemens.com/cs/ww/en/ps/3TK2040-3AN2/char>

**Further characteristics (e.g. electrical endurance, switching frequency)**

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3TK2040-3AN2&objecttype=14&gridview=view1>

last modified:

11/21/2022 