



!!! Phased-out product !!! The preferred successor is 3RQ2000-1BW00 coupling relay in industrial enclosure 2CO, Wide voltage 24...240 V AC/DC Screw terminals Width 22.5 mm

protection class IP

IP20

Substance Prohibitance (Date)

07/01/2006

operational current of auxiliary contacts at DC-13 at 230 V

0.1 A

ambient temperature during operation

-25 ... +60 °C

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TX7002-1CB00>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX7002-1CB00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7002-1CB00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX7002-1CB00&lang=en

Characteristic: Derating

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7002-1CB00/manual>

