



!!! Phased-out product !!! The preferred successor is 3RQ2000-1CW01
Coupling relay in industrial enclosure 2 CO, hard gold-plated contacts Wide
voltage range 24...240 V AC/DC

protection class IP

Substance Prohibitance (Date)

operational current of auxiliary contacts at DC-13 at 230 V

ambient temperature during operation

IP20

07/01/2006

0.1 A

-25 ... +60 °C

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TX7002-1FB02>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX7002-1FB02>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7002-1FB02>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX7002-1FB02&lang=en

Characteristic: Derating

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7002-1FB02/manual>

last modified:

12/23/2020 