



Digital monitoring relay Voltage monitoring, 22.5 mm from 17-275 V AC/DC  
 Overshoot and undershoot self-supplied Noise pulses delay 0.1 to 20 s  
 Hysteresis 0.1 to 150 V 1 changeover contact spring-type connection  
 system spring-type connection system

product brand name	SIRIUS
product designation	Voltage monitoring relay with digital setting
product type designation	3UG4
<b>General technical data</b>	
product function	Voltage monitoring relay
design of the display	LCD
insulation voltage for overvoltage category III according to IEC 60664	690 V
<ul style="list-style-type: none"> <li>with degree of pollution 3 rated value</li> </ul>	
type of voltage	AC/DC
<ul style="list-style-type: none"> <li>for monitoring</li> <li>of the control supply voltage</li> </ul>	AC/DC
surge voltage resistance rated value	4 kV
maximum permissible voltage for safe isolation	300 V
<ul style="list-style-type: none"> <li>between auxiliary and auxiliary circuit</li> <li>between control and auxiliary circuit</li> </ul>	300 V
protection class IP	IP20
shock resistance according to IEC 60068-2-27	sinusoidal half-wave 15g / 11 ms
vibration resistance according to IEC 60068-2-6	1 ... 6 Hz: 15 mm, 6 ... 500 Hz: 2g
mechanical service life (operating cycles) typical	10 000 000
electrical endurance (operating cycles) at AC-15 at 230 V typical	100 000
reference code according to IEC 81346-2	K
relative repeat accuracy	1 %
Substance Prohibitance (Date)	05/01/2012
<b>Product Function</b>	
product function	Yes
<ul style="list-style-type: none"> <li>undervoltage detection</li> <li>overvoltage detection</li> <li>overvoltage detection 1 phase</li> <li>overvoltage detection 3 phase</li> <li>overvoltage detection DC</li> <li>undervoltage detection 1 phase</li> <li>undervoltage detection 3 phases</li> <li>undervoltage detection DC</li> <li>voltage window recognition 1 phase</li> <li>voltage window recognition 3 phase</li> <li>voltage window recognition DC</li> <li>adjustable open/closed-circuit current principle</li> <li>external reset</li> <li>auto-RESET</li> </ul>	Yes Yes Yes No Yes Yes No Yes Yes No Yes Yes Yes Yes Yes Yes Yes
<b>Control circuit/ Control</b>	

<b>control supply voltage at AC</b>	
• at 50 Hz rated value	17 ... 275 V
• at 60 Hz rated value	17 ... 275 V
<b>control supply voltage at DC</b>	
• rated value	17 ... 275 V
<b>operating range factor control supply voltage rated value at DC</b>	
• initial value	1
• full-scale value	1
<b>operating range factor control supply voltage rated value at AC at 50 Hz</b>	
• initial value	1
• full-scale value	1
<b>operating range factor control supply voltage rated value at AC at 60 Hz</b>	
• initial value	1
• full-scale value	1
<b>Measuring circuit</b>	
<b>measurable line frequency</b>	500 ... 40 Hz
<b>measurable voltage at AC</b>	17 ... 275 V
<b>measurable voltage at DC</b>	17 ... 275 V
<b>adjustable response delay time</b>	
• when starting	0.1 ... 20 s
• with lower or upper limit violation	0.1 ... 20 s
<b>accuracy of digital display</b>	+/-1 digit
<b>relative temperature-related measurement deviation</b>	0.1 %
<b>Precision</b>	
<b>relative metering precision</b>	5 %
<b>Auxiliary circuit</b>	
number of NC contacts delayed switching	0
number of NO contacts delayed switching	0
number of CO contacts delayed switching	1
<b>operating frequency with 3RT2 contactor maximum</b>	5 000 1/h
<b>Main circuit</b>	
<b>number of poles for main current circuit</b>	1
ampacity of the output relay at AC-15 at 400 V at 50/60 Hz	3 A
<b>ampacity of the output relay at DC-13</b>	
• at 24 V	1 A
• at 125 V	0.2 A
• at 250 V	0.1 A
<b>operational current at 17 V minimum</b>	5 mA
<b>continuous current of the DIAZED fuse link of the output relay</b>	4 A
<b>Electromagnetic compatibility</b>	
<b>conducted interference</b>	
• due to burst according to IEC 61000-4-4	2 kV
• due to conductor-earth surge according to IEC 61000-4-5	2 kV
• due to conductor-conductor surge according to IEC 61000-4-5	1 kV
<b>field-based interference according to IEC 61000-4-3</b>	10 V/m
<b>electrostatic discharge according to IEC 61000-4-2</b>	6 kV contact discharge / 8 kV air discharge
<b>Galvanic isolation</b>	
<b>design of the electrical isolation</b>	Protective separation
<b>galvanic isolation</b>	
• between input and output	Yes
• between the outputs	Yes
• between the voltage supply and other circuits	No
<b>Connections/ Terminals</b>	
<b>product component removable terminal for auxiliary and control circuit</b>	Yes
<b>type of electrical connection</b>	spring-loaded terminals
<b>type of connectable conductor cross-sections</b>	

- solid
- finely stranded with core end processing
- finely stranded without core end processing
- at AWG cables solid
- at AWG cables stranded

2x (0.25 ... 1.5 mm<sup>2</sup>)  
 2 x (0.25 ... 1.5 mm<sup>2</sup>)  
 2x (0.25 ... 1.5 mm<sup>2</sup>)  
 2x (24 ... 16)  
 2x (24 ... 16)

**connectable conductor cross-section**

- solid
- finely stranded with core end processing
- finely stranded without core end processing

0.25 ... 1.5 mm<sup>2</sup>  
 0.25 ... 1.5 mm<sup>2</sup>  
 0.25 ... 1.5 mm<sup>2</sup>

**AWG number as coded connectable conductor cross section**

- solid
- stranded

24 ... 16  
 24 ... 16

**Installation/ mounting/ dimensions**

<b>mounting position</b>	any
<b>fastening method</b>	snap-on mounting
<b>height</b>	94 mm
<b>width</b>	22.5 mm
<b>depth</b>	91 mm
<b>required spacing</b>	
• with side-by-side mounting	
— forwards	0 mm
— backwards	0 mm
— upwards	0 mm
— downwards	0 mm
— at the side	0 mm
• for grounded parts	
— forwards	0 mm
— backwards	0 mm
— upwards	0 mm
— at the side	0 mm
— downwards	0 mm
• for live parts	
— forwards	0 mm
— backwards	0 mm
— upwards	0 mm
— at the side	0 mm

**Ambient conditions**

installation altitude at height above sea level maximum	2 000 m
<b>ambient temperature</b>	
• during operation	-25 ... +60 °C
• during storage	85 ... -40 °C
• during transport	85 ... -40 °C

**Certificates/ approvals**

<b>General Product Approval</b>	<b>EMC</b>	<b>Declaration of Conformity</b>
---------------------------------	------------	----------------------------------

[Confirmation](#)



<b>Declaration of Conformity</b>	<b>Test Certificates</b>	<b>Marine / Shipping</b>	<b>other</b>
----------------------------------	--------------------------	--------------------------	--------------



[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)



[Confirmation](#)

**Railway**

Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UG4633-2AL30>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UG4633-2AL30>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<https://support.industry.siemens.com/cs/ww/en/ps/3UG4633-2AL30>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3UG4633-2AL30&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UG4633-2AL30&lang=en)

Characteristic: Derating

<https://support.industry.siemens.com/cs/ww/en/ps/3UG4633-2AL30/manual>



last modified:

11/29/2022