



circuit breaker 3VA5 UL frame 125 breaking capacity class H 65kA @ 480V  
3-pole, line protection TM230, FTAM,  $I_n=25A$  overload protection  $I_r=25A$   
fixed short-circuit protection  $I_i=6...12 \times I_n$  without connection

### Model

|                                                                                                                            |                             |
|----------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| product brand name                                                                                                         | SENTRON                     |
| product designation                                                                                                        | Molded-case circuit breaker |
| product designation / according to UL file                                                                                 | HEAS                        |
| design of the product                                                                                                      | System protection           |
| design of the load switch / according to UL 489 / Heating, Air Conditioning, and Refrigeration circuit breaker (HACR Type) | Yes                         |
| design of the load switch / according to UL 489 / High-Intensity-Discharge circuit breaker (HID Type)                      | Yes                         |
| design of the load switch / according to UL 489 / Switching Duty circuit breaker (SWD Type)                                | No                          |
| design of the overcurrent release                                                                                          | TM230                       |
| protection function of the overcurrent release                                                                             | LI                          |
| number of poles                                                                                                            | 3                           |

### General technical data

|                                                                                                       |          |
|-------------------------------------------------------------------------------------------------------|----------|
| insulation voltage / rated value                                                                      | 800 V    |
| Max. rated operational voltage $U_e$ with DC                                                          | 500 V    |
| operating voltage / at AC / rated value                                                               | 690 V    |
| power loss [W] / maximum                                                                              | 8.6 W    |
| Active power loss / for rated value of the current / at AC / in hot operating state / per pole        | 2.87 W   |
| mechanical service life (operating cycles) / typical                                                  | 20 000   |
| Electrical endurance (switching cycles) / at AC-1 / at 380/415 V 50/60 Hz                             | 8 000    |
| Electrical endurance (switching cycles) / at AC-1 / at 690 V 50/60 Hz                                 | 4 000    |
| electrical endurance (operating cycles) / at 480 V                                                    | 8 000    |
| electrical endurance (operating cycles) / at 600 V                                                    | 4 000    |
| product feature / for neutral conductors / upgradable/retrofitable / short-circuit and overload proof | No       |
| ground-fault monitoring version                                                                       | without  |
| product function                                                                                      |          |
| • communication function                                                                              | No       |
| • other measurement function                                                                          | No       |
| Net Weight                                                                                            | 0.963 kg |

### Current

|                                                    |      |
|----------------------------------------------------|------|
| marking / according to UL 489 / 100%-rated breaker | No   |
| operational current                                |      |
| • at 40 °C                                         | 25 A |
| • at 45 °C                                         | 24 A |
| • at 50 °C                                         | 24 A |
| • at 55 °C                                         | 23 A |

|            |      |
|------------|------|
| • at 60 °C | 23 A |
| • at 65 °C | 23 A |
| • at 70 °C | 22 A |

#### Switching capacity according to IEC 60947

|                                                         |                                                                                                                                                                |
|---------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| switching capacity class of the circuit breaker         | H                                                                                                                                                              |
| maximum short-circuit current breaking capacity (Icu)   |                                                                                                                                                                |
| • at 240 V                                              | 150 kA                                                                                                                                                         |
| • at 415 V                                              | 70 kA                                                                                                                                                          |
| • at 690 V                                              | 10 kA                                                                                                                                                          |
| operating short-circuit current breaking capacity (Ics) |                                                                                                                                                                |
| • at 240 V                                              | 150 kA                                                                                                                                                         |
| • at 415 V                                              | 70 kA                                                                                                                                                          |
| • at 690 V                                              | 5 kA                                                                                                                                                           |
| short-circuit current making capacity (Icm)             |                                                                                                                                                                |
| • at 240 V                                              | 330 kA                                                                                                                                                         |
| • at 415 V                                              | 154 kA                                                                                                                                                         |
| • at 690 V                                              | 17 kA                                                                                                                                                          |
| design of short-circuit protection                      | For switching power values in DC networks, see the 3VA molded case circuit breaker device manual; link to be found under Service & Support in the last chapter |

#### Switching capacity according to UL 489

|                           |        |
|---------------------------|--------|
| current breaking capacity |        |
| • at 240 V                | 150 kA |
| • at 480 V                | 65 kA  |
| • at 600 Y/347 V          | 25 kA  |

#### Adjustable parameters

|                                                                                                                   |             |
|-------------------------------------------------------------------------------------------------------------------|-------------|
| adjustable response value setting current (I <sub>r</sub> ) / of the L-trip / with I <sub>2t</sub> characteristic |             |
| • minimum                                                                                                         | 25 A        |
| • maximum                                                                                                         | 25 A        |
| adjustable response value delay time (t <sub>r</sub> ) / for L-tripping / with I <sub>2t</sub> characteristic     |             |
| • minimum                                                                                                         | 1 s         |
| • maximum                                                                                                         | 1 s         |
| adjustable response value setting current (I <sub>l</sub> ) / for I-tripping                                      |             |
| • minimum                                                                                                         | 150 A       |
| • maximum                                                                                                         | 300 A       |
| adjustable absolute value setting current (I <sub>nN</sub> ) / for N-tripping                                     |             |
| • minimum                                                                                                         | 0 A         |
| • maximum                                                                                                         | 0 A         |
| adjustable current response value current / of the current-dependent overload release                             | 25 ... 25 A |
| Ground fault protection / tripping switchable / I <sub>2t</sub> =ON/OFF                                           | No          |

#### Mechanical Design

|                        |         |
|------------------------|---------|
| product component      |         |
| • undervoltage release | No      |
| • voltage trigger      | No      |
| • trip indicator       | No      |
| height [in]            | 5.51 in |
| height                 | 140 mm  |
| width [in]             | 3 in    |
| width                  | 76.2 mm |
| depth [in]             | 3.01 in |
| depth                  | 76.5 mm |

#### Connections

|                                                                 |                    |
|-----------------------------------------------------------------|--------------------|
| arrangement of electrical connectors / for main current circuit | Without connection |
| type of electrical connection / for main current circuit        | Without            |

#### Auxiliary circuit

|                                                |   |
|------------------------------------------------|---|
| number of CO contacts / for auxiliary contacts | 0 |
|------------------------------------------------|---|

#### Accessories

|                                            |     |
|--------------------------------------------|-----|
| product extension / optional / motor drive | Yes |
|--------------------------------------------|-----|

## Environmental conditions

|                                    |        |
|------------------------------------|--------|
| protection class IP / on the front | IP40   |
| ambient temperature                |        |
| • during operation / minimum       | -25 °C |
| • during operation / maximum       | 70 °C  |
| • during storage / minimum         | -40 °C |
| • during storage / maximum         | 80 °C  |

## Certificates

|                                           |   |
|-------------------------------------------|---|
| reference code / according to IEC 81346-2 | Q |
|-------------------------------------------|---|

### General Product Approval



[Confirmation](#)



### General Product Approval

### EMC

### Declaration of Conformity

### Test Certificates

[Miscellaneous](#)



[Special Test Certificate](#)

### Test Certificates

### Marine / Shipping

### other

[Miscellaneous](#)



[Miscellaneous](#)

[Miscellaneous](#)

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA5125-6EC31-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA5125-6EC31-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA5125-6EC31-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA5125-6EC31-0AA0)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



CB



last modified:

7/14/2022 [🔗](#)

