



SHUNT TRIP FLEXIBLE 600 V AC 50/60 HZ ACCESSORY FOR 3VA4 and 3VA51 up to 3VA54 and 3VA61 up to 3VA64

| Model                                                                              |                   |
|------------------------------------------------------------------------------------|-------------------|
| product brand name                                                                 | SENTRON           |
| product designation                                                                | Accessories       |
| design of the product                                                              | Auxiliary release |
| accessories                                                                        | Auxiliary release |
| General technical data                                                             |                   |
| degree of pollution                                                                | 3                 |
| overvoltage category                                                               | III               |
| apparent power consumption / maximum                                               | 300 VA            |
| Voltage                                                                            |                   |
| surge voltage resistance                                                           | 4 kV              |
| Mechanical Design                                                                  |                   |
| height                                                                             | 65.1 mm           |
| width                                                                              | 21.7 mm           |
| number of slots                                                                    | 3                 |
| depth                                                                              | 31.2 mm           |
| net weight                                                                         | 91 g              |
| tightening torque / with screw-type terminals / minimum                            | 0.4 N·m           |
| tightening torque / with screw-type terminals / maximum                            | 0.5 N·m           |
| Connections according IEC                                                          |                   |
| stripped length                                                                    | 10 mm             |
| AWG number / as coded connectable conductor cross section / for auxiliary contacts |                   |
| • minimum                                                                          | 20                |
| • maximum                                                                          | 16                |
| Connections according UL                                                           |                   |
| stripped length [in]                                                               | 0.4 in            |
| tightening torque [lbf·in] / with screw-type terminals / minimum                   | 3.5 lbf·in        |
| tightening torque [lbf·in] / with screw-type terminals / maximum                   | 4.4 lbf·in        |

### Further information

#### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

#### Industry Mall (Online ordering system)


<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9978-0BA25>


#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA9978-0BA25>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA9978-0BA25](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9978-0BA25)





last modified:

12/20/2020 

