



Removable terminal 2-pole, screw terminals up to maximum 2 x 2.5 mm² or 1 x 4 mm², For SIRIUS devices in industrial standard mounting rail enclosure

product brand name
product category
product designation
design of the product

SIRIUS
Removable terminals
Terminal for main circuit/2-pole
Screw terminal/1 x 4 mm²

General technical data

protection class IP
Substance Prohibittance (Date)
type of connectable conductor cross-sections

- solid
- finely stranded with core end processing
- at AWG cables solid

width

IP20
03/01/2017
1x (0.5 ... 4.0 mm²), 2x (0.5 ... 2.5 mm²)
1x (0.5 ... 4 mm²), 2x (0.5 ... 1.5 mm²)
1x (20 ... 12), 2x (20 ... 14)
7.5 mm

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3ZY1122-1BA00>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3ZY1122-1BA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)



<https://support.industry.siemens.com/cs/ww/en/ps/3ZY1122-1BA00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3ZY1122-1BA00&lang=en

Characteristic: Derating

<https://support.industry.siemens.com/cs/ww/en/ps/3ZY1122-1BA00/manual>



last modified:

1/28/2021 