

# 440RN23122

AB 440R MSR Safety Relay R 115VAC 1NC/LC-IN 2NO-SFTY MM



Component type	Device for monitoring of safety-related circuits
Range	MSR
Model	N/A
Product status	Existing

The Allen-Bradley Single-Function and Specialty Relays are designed for small or single-zone safety applications. Ideal for safe speed control (MSR57), back EMF monitor (MSR55), safety control circuits involving light curtains, laser scanners, safety mats, interlock switches, guard locking interlocks, two-hand controls, safety edges, enabling devices and E-stop push buttons.

## ELECTRICAL

Rated operation current I <sub>e</sub>	6 A
Rated operation current I <sub>e</sub> at AC-15, 230 V	6 A
Rated operation current I <sub>e</sub> at DC-13, 24 V	3 A
Voltage type for actuating	AC
Control supply voltage U <sub>s</sub> at AC 50HZ	115 V
Safety category according to EN ISO 13849-1	4
Number of outputs, safety related, undelayed, with contact	2

## CONSTRUCTION

Performance level according to EN ISO 13849-1	Level e
Rail mounting possible	Yes
Degree of protection (IP)	IP40
Degree of protection (IP), terminals	IP20

## MECHANICAL

Max. shock acceleration	10 g
Max. vibration displacement (Pk-Pk)	0.35 mm
Max. vibration frequency, operational	55 Hz

## DIMENSIONS

Width	22.5 mm
Height	75 mm
Depth	110 mm
Weight	0.22

## ENVIRONMENT

Ambient temperature during operating	-5...55 °C
--------------------------------------	------------