

Specifications

Photo is representative

Eaton 045225

Eaton Moeller® series T3 On-Off switch, T3, 32 A, flush mounting, 3 contact unit(s), 6 pole, with black thumb grip and front plate

General specifications

PRODUCT NAME	Eaton Moeller® series T3 On-off switch
CATALOG NUMBER	045225
EAN	4015080452256
PRODUCT LENGTH/DEPTH	102 mm
PRODUCT HEIGHT	54 mm
PRODUCT WIDTH	61 mm
PRODUCT WEIGHT	0.212 kg
CERTIFICATIONS	CE CSA IEC/EN 60947-3 UL Category Control No.: NLRV CSA-C22.2 No. 60947-4-1- 14 IEC/EN 60204 IEC/EN 60947 CSA-C22.2 No. 94 CSA File No.: 012528 UL 60947-4-1 UL VDE 0660 CSA Class No.: 3211-07 UL File No.: E36332
CATALOG NOTES	Rated Short-time Withstand Current (Icw) for a time of 1 second
MODEL CODE	T3-3-8342/E

Features & Functions

FITTED WITH:	Black thumb grip and front plate
INSCRIPTION	0-1
NUMBER OF POLES	6

General

DEGREE OF PROTECTION	NEMA 12
DEGREE OF PROTECTION (FRONT SIDE)	IP65
LIFESPAN, MECHANICAL	500,000 Operations
MOUNTING METHOD	Flush mounting
MOUNTING POSITION	As required
NUMBER OF CONTACT UNITS	3
OPERATING FREQUENCY	1200 Operations/h
OVERTVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	On-Off switch
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
SAFE ISOLATION	440 V AC, Between the contacts, According to EN 61140
SAFETY PARAMETER (EN ISO 13849-1)	B10d values as per EN ISO 13849-1, table C.1
SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms
SUITABLE FOR	Branch circuits, suitable as motor disconnect, (UL/CSA) Front mounting 4-hole
SWITCHING ANGLE	90 °

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	50 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Terminal capacities

TERMINAL CAPACITY	2 x (0.75 - 4) mm ² , flexible with ferrules to DIN 46228 2 x (1 - 6) mm ² , solid or stranded 14 - 10 AWG, solid or flexible with ferrule 1 x (0.75 - 4) mm ² , flexible with ferrules to DIN 46228 1 x (1 - 6) mm ² , solid or stranded
SCREW SIZE	M4, Terminal screw
TIGHTENING TORQUE	17.7 lb-in, Screw terminals 1.6 Nm, Screw terminals

Electrical rating

RATED BREAKING

CAPACITY AT 220/230 V 260 A
(COS PHI TO IEC 60947-3)

RATED BREAKING

CAPACITY AT 400/415 V 260 A
(COS PHI TO IEC 60947-3)

RATED BREAKING

CAPACITY AT 500 V (COS PHI TO IEC 60947-3) 240 A

RATED BREAKING

CAPACITY AT 660/690 V (COS PHI TO IEC 60947-3) 170 A

RATED OPERATIONAL

CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V 23.7 A

RATED OPERATIONAL

CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V 23.7 A

RATED OPERATIONAL

CURRENT (IE) AT AC-3, 500 V 23.7 A

RATED OPERATIONAL

CURRENT (IE) AT AC-3, 660 V, 690 V 14.7 A

RATED OPERATIONAL

CURRENT (IE) AT AC-21, 440 V 32 A

RATED OPERATIONAL

CURRENT (IE) AT AC-23A, 230 V 32 A

RATED OPERATIONAL

CURRENT (IE) AT AC-23A, 400 V, 415 V 32 A

RATED OPERATIONAL

CURRENT (IE) AT AC-23A, 500 V 26.4 A

RATED OPERATIONAL

CURRENT (IE) AT AC-23A, 690 V 17 A

RATED OPERATIONAL

CURRENT (IE) AT DC-1, LOAD-BREAK SWITCHES L/R = 1 MS 25 A

RATED OPERATIONAL

CURRENT (IE) AT DC-13, CONTROL SWITCHES L/R = 50 MS 20 A

RATED OPERATIONAL

CURRENT (IE) AT DC-21, 1 A

Short-circuit rating

RATED CONDITIONAL

SHORT-CIRCUIT CURRENT (IQ) 1 kA

RATED SHORT-TIME

WITHSTAND CURRENT (ICW) 0.65 kA
650 A, Contacts, 1 second

SHORT-CIRCUIT CURRENT

RATING (BASIC RATING) 5 kA, SCCR (UL/CSA)
40A, max. Fuse, SCCR (UL/CSA)

SHORT-CIRCUIT CURRENT

RATING (HIGH FAULT) 40 A, Class J, max. Fuse,
SCCR (UL/CSA)
10 kA, SCCR (UL/CSA)

SHORT-CIRCUIT

PROTECTION RATING 35 A gG/gL, Fuse, Contacts

240 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A, 25 A

24 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A, 25 A

48 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A, 25 A

60 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A, 12 A

120 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A, 5 A

240 V

RATED OPERATIONAL

CURRENT (IE) STAR- 32 A

DELTA AT AC-3, 220/230 V

RATED OPERATIONAL

CURRENT (IE) STAR- 32 A

DELTA AT AC-3, 380/400 V

RATED OPERATIONAL

CURRENT (IE) STAR- 32 A

DELTA AT AC-3, 500 V

RATED OPERATIONAL

CURRENT (IE) STAR- 25.5 A

DELTA AT AC-3, 690 V

RATED OPERATIONAL

POWER AT AC-3, 380/400 11 kW

V, 50 HZ

RATED OPERATIONAL

POWER AT AC-3, 415 V, 50 11 kW

HZ

RATED OPERATIONAL

POWER AT AC-3, 690 V, 50 11 kW

HZ

RATED OPERATIONAL

POWER AT AC-23A, 7.5 kW

220/230 V, 50 HZ

RATED OPERATIONAL

POWER AT AC-23A, 15 kW

50 HZ

RATED OPERATIONAL

POWER AT AC-23A, 15 kW

50 HZ

RATED OPERATIONAL

POWER AT AC-23A, 15 kW

50 HZ

RATED OPERATIONAL

POWER AT AC-23A, 7.5 kW

POWER STAR-DELTA AT**220/230 V, 50 HZ****RATED OPERATIONAL****POWER STAR-DELTA AT** 15 kW
380/400 V, 50 HZ**RATED OPERATIONAL****POWER STAR-DELTA AT** 18.5 kW
500 V, 50 HZ**RATED OPERATIONAL****POWER STAR-DELTA AT** 22 kW
690 V, 50 HZ**RATED OPERATIONAL****VOLTAGE (UE) AT AC -** 690 V
MAX**RATED UNINTERRUPTED****CURRENT (IU)** 32 A**UNINTERRUPTED**
CURRENTRated uninterrupted
current lu is specified for
max. cross-section.

Switching capacity

$2 \times I_e$ (with intermittent operation class 12, 25 % duty factor)

$1.3 \times I_e$ (with intermittent operation class 12, 60 % duty factor)

$1.6 \times I_e$ (with intermittent operation class 12, 40 % duty factor)

LOAD RATING

NUMBER OF CONTACTS

IN SERIES AT DC-21A, 240

1

V

NUMBER OF CONTACTS

IN SERIES AT DC-23A, 24 V

1

NUMBER OF CONTACTS

IN SERIES AT DC-23A, 48 V

2

NUMBER OF CONTACTS

IN SERIES AT DC-23A, 60 V

3

NUMBER OF CONTACTS

IN SERIES AT DC-23A, 120

3

V

NUMBER OF CONTACTS

IN SERIES AT DC-23A, 240

5

V

SWITCHING CAPACITY

(MAIN CONTACTS,
GENERAL USE)

25 A, Rated uninterrupted current max. (UL/CSA)

SWITCHING CAPACITY

(AUXILIARY CONTACTS,
GENERAL USE)

10A, IU, (UL/CSA)

SWITCHING CAPACITY

(AUXILIARY CONTACTS,
PILOT DUTY)

P600 (UL/CSA)
A600 (UL/CSA)

RATED MAKING

CAPACITY UP TO 690 V

(COS PHI TO IEC/EN

60947-3)

320 A

VOLTAGE PER CONTACT

PAIR IN SERIES

60 V

Motor rating

ASSIGNED MOTOR

POWER AT 115/120 V, 60 HZ, 1-PHASE

1.5 HP

ASSIGNED MOTOR

POWER AT 200/208 V, 60 HZ, 1-PHASE

3 HP

ASSIGNED MOTOR

POWER AT 200/208 V, 60 HZ, 3-PHASE

3 HP

ASSIGNED MOTOR

POWER AT 230/240 V, 60 HZ, 1-PHASE

3 HP

ASSIGNED MOTOR

POWER AT 230/240 V, 60 HZ, 3-PHASE

3 HP

ASSIGNED MOTOR

POWER AT 460/480 V, 60 HZ, 3-PHASE

7.5 HP

ASSIGNED MOTOR

POWER AT 575/600 V, 60 HZ, 3-PHASE

10 HP

Contacts

CONTROL CIRCUIT RELIABILITY 1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)

NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS) 0

NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS) 0

NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS) 0

Actuator

ACTUATOR COLOR	Black
ACTUATOR FUNCTION	Maintained
ACTUATOR TYPE	Short thumb-grip

Design verification

EQUIPMENT HEAT

DISSIPATION, CURRENT- 0 W

DEPENDENT PVID

HEAT DISSIPATION 0 W
CAPACITY PDISS

HEAT DISSIPATION PER
POLE, CURRENT- 1.1 W
DEPENDENT PVID

RATED OPERATIONAL
CURRENT FOR SPECIFIED 32 A
HEAT DISSIPATION (IN)

STATIC HEAT
DISSIPATION, NON- 0 W
CURRENT-DEPENDENT
PVS

**10.2.2 CORROSION
RESISTANCE** Meets the product
standard's requirements.

**10.2.3.1 VERIFICATION OF
THERMAL STABILITY OF
ENCLOSURES** Meets the product
standard's requirements.

**10.2.3.2 VERIFICATION OF
RESISTANCE OF
INSULATING MATERIALS
TO NORMAL HEAT** Meets the product
standard's requirements.

**10.2.3.3 RESIST. OF
INSUL. MAT. TO
ABNORMAL HEAT/FIRE
BY INTERNAL ELECT.
EFFECTS** Meets the product
standard's requirements.

**10.2.4 RESISTANCE TO
ULTRA-VIOLET (UV)
RADIATION** UV resistance only in
connection with protective
shield.

10.2.5 LIFTING Does not apply, since the
entire switchgear needs to
be evaluated.

**10.2.6 MECHANICAL
IMPACT** Does not apply, since the
entire switchgear needs to
be evaluated.

10.2.7 INSCRIPTIONS Meets the product
standard's requirements.

**10.3 DEGREE OF
PROTECTION OF
ASSEMBLIES** Does not apply, since the
entire switchgear needs to
be evaluated.

**10.4 CLEARANCES AND
CREEPAGE DISTANCES** Meets the product
standard's requirements.

**10.5 PROTECTION
AGAINST ELECTRIC
SHOCK** Does not apply, since the
entire switchgear needs to
be evaluated.

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

BROCHURES [Brochure - T Rotary Cam switch and P Switch-disconnector](#)

CATALOGUES [P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN](#)

DECLARATIONS OF CONFORMITY [DA-DC-00004894.pdf](#) [DA-DC-00004923.pdf](#)

DRAWINGS [eaton-rotary-switches-mounting-t3-changeover-switch-dimensions-019.eps](#)

eaton-rotary-switches-front-plate-t0-on-off-switch-symbol-002.eps	
eaton-rotary-switches-mounting-t0-changeover-switch-3d-drawing-002.eps	
eaton-general-rotary-switch-t0-step-switch-symbol-002.eps	
ECAD MODEL	ETN.045225.edz
INSTALLATION INSTRUCTIONS	IL03801020Z
INSTALLATION VIDEOS	Eaton's P Switch-disconnectors used in a factory
MCAD MODEL	DA-CD-t3_3_e DA-CS-t3_3_e
PRODUCT NOTIFICATIONS	MZ008006ZU_Orderform_Customized_Switch.pdf MZ008005ZU_Orderform_Customized_Switch.pdf
WIRING DIAGRAMS	eaton-rotary-switches-on-off-switch-t0-on-off-switch-wiring-diagram-003.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
[Eaton.com](#)

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

