

Pilot devices, Ø 22 mm – Accessories



Description	Type	Order Code	Weight, kg
Flashing LED			
A lamp changing tool is required for changing bulb. Choose the same color for the LED and the lamp cap or use a clear lamp cap. The lamp base has to be connected to cathode (-) and the bottom contact to anode (+).			
Rated voltage 24 V, rated current 25 mA, DC			
	Wave length nm	Service life hours	
Red	630	50 000	4950 512-1 0.005
Green	565	50 000	4950 512-2 0.005
Yellow	585	50 000	4950 512-3 0.005
Lamp changing tool			
For LEDs and for bulbs	KA1-8072	1SFA 616 920 R8072	0.002
Mounting tool			
Used for tightening the sleeve	MA1-8015	1SFA 611 920 R8015	0.021
Membrane of rubber			
Of transparent, heat and cold resistant rubber. Does not harden at low temperature. Gives IP 67 degree of protection. When membrane is used, remove the gasket.			
For flush button	KA1-8052	1SFA 616 920 R8052	0.002
For extended button	KA1-8002	1SFA 616 920 R8002	0.002
Emergency stop shroud Not for use with plastic enclosure			
For 40 mm Emergency Stop Pushbuttons. To prevent inadvertant operation.			
Yellow	KA1-8053	1SFA 616 920 R8053	0.020
Protective ring			
For flush and extended buttons To prevent inadvertant operation. Not together with legend plate holder.			
		SK 615 512-1	0.002
Protective cover			
For flush button. To prevent inadvertant operation. Not together with legend plate holder.			
	KA1-8010	1SFA 616 920 R8010	0.008
Bezel (Packing unit 10 pieces)			
For pushbutton			
Grey, plastic	KA1-8079	1SFA 616 920 R8079	0.025
Black, plastic	KA1-8022	1SFA 616 920 R8022	0.025
Metal	KA1-8021	1SFA 616 920 R8021	0.025
For modular selector switch			
Grey, plastic	KA1-8077	1SFA 616 920 R8077	0.020
Black, plastic	KA1-8080	1SFA 616 920 R8080	0.025
Metal	KA1-8024	1SFA 616 920 R8024	0.025
For compact selector switch			
Grey	CA1-8076	1SFA 619 920 R8076	0.001
Black	CA1-8077	1SFA 619 920 R8077	0.001
Metal	CA1-8078	1SFA 619 920 R8078	0.005