

Starter/Contactor Auxiliary Contact Kits

Description	Class	Size	Type	Catalog Number	List Price \$
	14, 17, 18, 22, 25, 26, 30, 32, 36, 37, 40, 43, 83, 84, 87, 88	00-4	1 NO	49AB10	
			1 NC	49AB01	
			1 NC Early Break	49AB01EB	
			1 NC Late Break	49AB01LB	
			1 NC Extra Late Break	49AB01XLB	
			1 NO Extra Late Make	49AB10XLM	
			1 NO & 1 NC	49AB11	
			2 NO	49AB20	
			4 NO	49AB40 ^⑤	
			3 NO & 1 NC	49AB31 ^⑤	
			2 NO & 2 NC	49AB22 ^⑤	
	14, 17, 18, 22, 25, 26, 36, 37, 40, 43, 87, 88	5, 6	2 NO	3RH1921-1EA20 ^②	
			1 NO & 1 NC	3RH1921-1DA11 ^②	
			2 NC	3RH1921-1EA02 ^②	
	14, 17, 18, 22, 25, 26, 40, 43	7, 8	1 NO & 1 NC (Inside L or R)	49CAL18-11	
			1 NO & 1 NC (Outside L or R)	49CAL18-11B	
	LEN, LED, LEF, LEB	20-60 Amps	1 NO	49ACR0	
			1 NC	49ACRC	
			2 NO	49ACR7	
			1 NO & 1 NC	49ACR6	
		100 Amps	2 NC	49ACR8	
			1 NO	49D22125001	
			1 NC	49D22125002	
		200-400 Amps	1 NO/NC SPDT	49CE42SPDT	
			1 NO/NC SPDT	3RH1921-1DA11 ^②	
	CLM, CMN, CMF, CMB	20 Amps	1 NO/NC SPDT	CLM4097291	
			2 NO/NC SPDT	CLM4097292	
		30-200 Amps	1 NO & 1 NC	CLMFCAK11	
			2 NC	CLMFCAK02	
			2 NO	CLMFCAK20	
			1 Coil Clearing NO & NC	CLMFCK11	
		300-400 Amps	1 NO & 1 NC	CLMHCAK11	
			2 NC	CLMHCAK02	
			2 NO	CLMHCAK20	
			1 Coil Clearing NO & NC	CLMHCK11	

Disconnect Auxiliary Switch Kits

Description	Class	Disconnect Amp or CB Rating	Type	Catalog Number	List Price \$
Non-fusible or Fusible Type	17, 25, 32, 37, 83, 84, 87, 88, LED, LEF, CMN, CMF	30 - 200A	2 NO/2 NC DPDT (NEMA A600)	HA261234	
MCP	18, 26, 32, 37, 83, 84, 87, 88, LEB, CMB	3A-125A	1 NO/1 NC 240V	A02ED62 ^③	
		250A	1 NO/1 NC 480V	A02FD64 ^③	
		400A-600A	(2) 1 NO/1 NC SPDT-480V	A02JLD64 ^③	

Control Power Transformer Kits^{①④}

Description	Recommended Transformer Size		VA Rating	Catalog Number	List Price \$	Transformer Table		
	Control Size	Transformer VA				Primary Volts	Secondary Volts	Code
 Transformer 50/60HZ	00-2½	45 or 50 ^⑤	45 VA	KT*050 ^{②④}		120	24	1
	3-3½	75	50 VA	KT*050P ^④		208	24	G
	4	100	100 VA	KT*100		208	120	H
	5-6	150	150 VA	KT*150		240/480	24	4
	7-8	300	200 VA	KT*200		240/480	120	8
	Lighting Control		300 VA	KT*300		277	24	5
	CLM	20A, 2 - 12P	500 VA	KT*500		277	120	7
		30A, 3P				600	24	6
		30A, 6 - 12P				600	120	9
		60A, 3P						
		60A, 4 - 6P						
		60A, 8 - 12P						
	LEN	100/200A, 3P						
		100/200A, 5P						
		300/400A, 3P						
		20A, 3 - 12P						
		30/60A, 3 - 6P						
		30/60A, 9 - 12P						
		100/200A, 3P						
		100/200A, 5P						
		300/400A, 3P						

① Installation of CPTs may require a larger enclosure.
② 45VA transformer kits will include secondary but not primary fusing. Sizes 50VA and higher include

2-pole primary fusing and 1-pole secondary fusing.
③ Product Category: MCCB.

④ For 24VAC control a minimum of 100VA CPT is required.
⑤ Assembled at the factory.