



Figure similar

Auxiliary contact kit class LC electrically held lighting contact form C (spdt) rating 600, 24VDC

product brand name	Class LC
design of the product	2 Normally Closed
product type designation	Aux contacts
special product feature	For use on Class LC lighting contactors

General technical data

weight [lb]	0.3 lb
Height x Width x Depth [in]	1.85 x 1.5 x 0.4 in
touch protection against electrical shock	finger-safe
ambient temperature [°F]	
• during storage	-22 ... +149 °F
• during operation	-13 ... +104 °F
ambient temperature	
• during storage	-30 ... +65 °C
• during operation	-25 ... +40 °C
country of origin	Poland

Contact block

number of NC contacts / for auxiliary contacts	2
number of NO contacts / for auxiliary contacts	2

Mounting/wiring

fastening method	snap-on mounting
type of electrical connection	screw-type terminals
tightening torque [lbf·in] / with screw-type terminals	7 ... 12 lbf·in
type of connectable conductor cross-sections / at AWG	2x (22 ... 12 AWG)
cables / for control connection / with screw-type terminals / single or multi-stranded	
temperature / of the conductor / for control connection / with screw-type terminals / maximum permissible	75 °C
material / of the conductor	CU

Certificates/ approvals

certificate of suitability	cULus
----------------------------	-------

Further information

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:49LCAC2PA>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:49LCAC2PA>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_us.aspx?mlfb=US2:49LCAC2PA&lang=en

