## **SIEMENS**

Data sheet US2:49SAS04

## SELECTOR SWITCH"A4" OFF-ON



product brand name	Enclosed Control Product Accessories
design of the product	OFF-ON Selector Switch
product type designation	Pilot device
special product feature	For use in enclosures with hinged cover.
General technical data	
weight [lb]	0.35 lb
Height x Width x Depth [in]	2.1 × 2 × 3.94 in
touch protection against electrical shock	finger-safe
ambient temperature [°F]	inigor outo
during storage	-40 +185 °F
during operation	-31 +158 °F
ambient temperature	
during storage	-40 +85 °C
during operation	-35 +70 °C
country of origin	Mexico
material / of the front ring	Metal with chrome plating
accessories / included	Wires
Actuator	
diameter	30 mm
design of the actuating element	Short lever
material / of the actuating element	Plastic
color / of the actuating element	White foreground / Black background
product function / illumination	No
number of switching positions	2
mechanical service life (operating cycles) / typical	2 000 000
Contact block	
number of NC contacts / for auxiliary contacts	0
number of NO contacts / for auxiliary contacts	1
design of the contact / of auxiliary contacts	Silver with no plating
Legend	
material	Brushed aluminum
marking / of inscription plate	OFF ON
color / of inscription plate	Aluminum foreground / Black background
Mounting/wiring	
fastening method	rear mounting
type of electrical connection	screw-type terminals
tightening torque [lbf-in] / with screw-type terminals	7 9 lbf-in
type of connectable conductor cross-sections / for AWG cables / for control connection / with screw-type terminals / single or multi-stranded	2x (18 12 AWG)
temperature / of the conductor / for control connection / with	75 °C

last modified:	9/18/2022 🗗	
https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:49SAS04 Service&Support (Manuals, Certificates, Characteristics, FAQs,) https://support.industry.siemens.com/cs/ww/en/ps/US2:49SAS04 Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,) http://www.automation.siemens.com/bilddb/cax_us.aspx?mlfb=US2:49SAS04⟨=en		
Industry Mall (Online ordering system)		
Further information		
certificate of suitability	cULus	
Certificates/ approvals		
material / of the conductor	CU	
screw-type terminals / maximum permissible		