

THERMOMARK CARD - Thermal transfer printer



5146464

<https://www.phoenixcontact.com/us/products/5146464>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Thermal transfer printer for cards



Product description

The THERMOMARK CARD prints marking materials in card format for terminal marking, wire and cable marking, and equipment and plant marking to an incredibly high quality.

Your advantages

- Maintenance-free operation with proven thermal transfer printer technology
- High-quality, fast labeling. Printing time for one UniCard: just 8 seconds.
- Easy operating concept based on user-friendly touch screen entry
- Easy to control with the PROJECT COMPLETE software

Commercial data

Item number	5146464
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BG01
Product key	BG1221
Catalog page	Page 42 (C-3-2017)
GTIN	4046356528795
Weight per piece (including packing)	9,820 g
Weight per piece (excluding packing)	9,200 g
Customs tariff number	84433210
Country of origin	DE

THERMOMARK CARD - Thermal transfer printer



5146464

<https://www.phoenixcontact.com/us/products/5146464>

Technical data

Product properties

Product type	Printing system
--------------	-----------------

Marking

Identification technology	Thermal transfer for sheets and cards
---------------------------	---------------------------------------

Device properties

Print width	104 mm
Print resolution	300 dpi
Operating system	MS Windows Vista, MS Windows 7 (32/64-bit), MS Windows 8 (32/64-bit), MS Windows 8.1 (32/64-bit), MS Windows 10 (32/64-bit), Server 2008, Server 2008 R2, Server 2012, Server 2012 R2

Electrical properties

Supply

Supply voltage range	100 V AC ... 240 V AC (50 Hz ... 60 Hz)
----------------------	---

Interfaces

Interface	10/100 Mbps Ethernet
Interface	USB 2.0

Dimensions

Width	254 mm
Height	194 mm
Length	325 mm

Material specifications

Color	gray
-------	------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	5 °C ... 35 °C
Permissible humidity (operation)	10 % ... 80 %

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com