SIEMENS

Data sheet US2:52BP3BS



30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Push-Pull Operator Full Voltage, 6V AC/DC Incandescent Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic, Green 3 Position Momentary UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product	Actuator round
Enclosure	
number of command points	1
delivery state as a kit	No
Actuator	
product extension optional light source	Yes
material of the actuating element	plastic
type of unlocking device	without
number of switching positions	3
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	black
Holder	
material of the holder	Metal
Contact block/ lampholder	
socket design	BA 9s with lamp
number of lampholders	1
Display	
number of LED modules	0
General technical data	
product component	
lamp transformer	No
• light source	Yes
de avec of mellistics	res
degree of pollution	1
type of voltage	
type of voltage	1
type of voltage • of the operating voltage	1 AC/DC
type of voltage	AC/DC AC/DC
type of voltage of the operating voltage of the input voltage surge voltage resistance rated value	1 AC/DC AC/DC 4 kV
type of voltage	AC/DC AC/DC 4 kV IP66
type of voltage of the operating voltage of the input voltage surge voltage resistance rated value protection class IP of the terminal	AC/DC AC/DC 4 kV IP66
type of voltage	1 AC/DC AC/DC 4 kV IP66 IP20
type of voltage	1 AC/DC AC/DC 4 kV IP66 IP20 6 8 V
type of voltage	1 AC/DC AC/DC 4 kV IP66 IP20 6 8 V
type of voltage	1 AC/DC AC/DC 4 kV IP66 IP20 6 8 V 6 8 V
type of voltage of the operating voltage of the input voltage surge voltage resistance rated value protection class IP of the terminal operating voltage of the derivative at AC at 60 Hz rated value supply voltage type of voltage of the supply voltage of the light source	1 AC/DC AC/DC 4 kV IP66 IP20 6 8 V 6 8 V

• rated value	8 6 V
Connections/ Terminals	
type of electrical connection	screw-type terminals
 of modules and accessories 	Screw-type terminal
tightening torque of the screws in the bracket	20 N·m
tightening torque [lbf·in] with screw-type terminals	8 8 lbf-in
Lamp	
type of light source	filament lamp
color of the light source	clear
Safety related data	
touch protection against electrical shock	finger-safe
Ambient conditions	
ambient temperature	
 during operation 	-35 +70 °C
during storage	-40 +85 °C
Installation/ mounting/ dimensions	
shape of the installation opening	round
Certificates/ approvals	
Further information	

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

all.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52BP3BS

Cax online generator

 $\underline{\text{http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en\&mlfb=US2:52BP3BS}$

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/US2:52BP3B

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52BP3BS&lang=en

last modified:	5/31/2021