SIEMENS

Data sheet

US2:52BP3G9XB



30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Push-Pull Operator Transformer type, 120V AC LED Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Metal, Black with Amber Lens 3 Position Momentary UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product Actuator round Enclosure I number of command points 1 delivery state as a kit No Actuator amber color of the actuating element amber material of the actuating element amber material of the actuating element amber reader and the actuating element without number of switching positions 3 Front ring Yes design of the front ring standard material of the front ring metal color of the front ring standard material of the front ring black Holder Metal color of the front ring black Holder metal numbrid material of the holder Metal Contract block/ lampholder action of lampholder socket design BA 9s with LED number of lampholders 1 Obspiay number of lampholder e light source Yes e light source Yes e of the operating voltage AC of the operating voltage AC e of the input voltage of the light source AC surge voltage of the light source AC <th></th> <th></th>		
number of command points 1 delivery state as a kit No Actuator Product extension optional light source Yes product extension optional light source Yes color of the actuating element amber material of the actuating element metal mushroom head with plastic lens type of unlocking device without number of switching positions 3 product component front ring yes design of the front ring standard material of the front ring black tolder material of the front ring material of the holder Metal Contact block/ lampholder socket design number of LED modules 1 Display Indexed and and and and and and and and and an	design of the product	Actuator round
delivery state as a kit No Actuator	Enclosure	
Actuator Product extension optional light source Yes color of the actuating element amber material of the actuating element metal mushroom head with plastic lens type of unlocking device without number of switching positions 3 Product component front ring Yes design of the front ring standard material of the front ring black Holder Metal color of the front ring black Holder Metal contact block/ lampholder socket design number of LED modules 1 General technical data 1 product component Yes i lamp transformer Yes i lamp transformer Yes i lamp transformer Yes of the operating voltage AC of the operating voltage AC of the input voltage AC surge voltage resistance rated value Holder surge voltage of the light source AC surge voltage of the light source AC surge voltage of the light source AC </td <td>number of command points</td> <td>1</td>	number of command points	1
product extension optional light source Yes color of the actuating element amber material of the actuating element method imper of witching device without number of switching positions 3 Front ring Yes design of the front ring Yes design of the front ring standard color of the front ring black Holder Metal Contract block/ lampholders 0 socket design BA 9s with LED number of LED modules 1 General tochnical data product component product component Yes e light source Yes degree of pollution 1 type of voltage AC of the operating voltage AC of the operating voltage AC of the operating voltage AC of the terminal IP20 Surger voltage of the supply voltage of the light source AC surger voltage of the supply voltage of the light source AC supply volta	delivery state as a kit	No
color of the actuating element amber matarial of the actuating element metal mushroom head with plastic lens type of unclocking device without number of switching positions 3 Front ring Yes design of the front ring metal color of the front ring block Holder Metal Contact block/ lampholder socket design socket design BA 9 swith LED number of LED modules 1 Ceneral technical data product component of the operating voltage Yes e light source Yes of the operating voltage AC of the operating voltage AC of the input voltage AC surge voltage resistance rated value 4 kV protect colage of the light source AC surge voltage resistance rated value 6 V outgut voltage 1 of the light source rated value 6 V	Actuator	
material of the actuating element metal mushroom head with plastic lens type of unlocking device without number of switching positions 3 Front ring Yes design of the front ring standard material of the front ring metal color of the front ring metal color of the front ring black Holder material of the holder Contact block/ lampholder standard socket design BA 9s with LED number of LED modules 1 Objeplay	product extension optional light source	Yes
type of unlocking device without number of switching positions 3 Front ring product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder Metal Contract block/ lampholder Socket design socket design BA 9s with LED number of LED modules 1 General technical data Product component e light source Yes e light source Yes of the operating voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 e of the terminal IP20 Supply voltage AC surge voltage of the light source AC surge voltage of the light source at AC at 60 Hz 6 V inputs/of/optus 6 V	color of the actuating element	amber
number of switching positions 3 Pront ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder metal color of the holder Metal Contact block/ lampholder socket design socket design BA 9s with LED number of lampholders 1 Display Image: Component • lamp transformer Yes • light source Yes degree of pollution 1 type of voltage AC • of the input voltage AC • of the input voltage AC • of the terminal IP20 Supply voltage of the light source AC • of the terminal IP20 Supply voltage AC • of the light source at AC at 60 Hz 6 V • at ad value 6 V Inputs/ Cutputs 6 V	material of the actuating element	metal mushroom head with plastic lens
Front ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder Metal Contact block/lampholder socket design socket design BA 9s with LED number of LED modules 1 General technical data general technical data product component Yes • light source Yes degree of pollution 1 type of voltage AC • of the input voltage AC • of the terminal IP20 Supply voltage of the light source AC stupply voltage of the light source AC • of the input voltage of the light source AC • of the terminal IP20 Supply voltage of the light source AC • portage of the light source AC • of the learninal IP20 Supply voltage of the light source AC • of the learninal IP20 Supply voltage of the light source AC • rated value 6 V <tr< td=""><td>type of unlocking device</td><td>without</td></tr<>	type of unlocking device	without
product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder Metal Contact block/ lampholder socket design socket design BA 9s with LED number of lampholders 1 Display Immber of LED modules number of LED modules 1 general technical data Immber of lamp transformer ves light source Yes e light source Yes of the input voltage AC of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 of the lempinal IP20 Supply voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V Inputs/ Outputs 6 V	number of switching positions	3
design of the front ring standard material of the front ring black Holder material of the nolder material of the holder Metal Contact block/ lampholder socket design socket design BA 9s with LED number of LED modules 1 Display number of LED modules number of LED modules 1 General technical data Yes product component Yes • light source Yes • of the operating voltage AC • of the operating voltage AC • of the input voltage AC • of the input voltage AC • of the terminal IP60 • of the terminal IP20 Supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz Filter of all of the lamp transformer rated value • rated value 6 V Inputs/ Outputs 6 V	Front ring	
material of the front ring metal color of the front ring black Holder material of the holder material of the holder Metal Contact block/lampholder socket design socket design BA 9s with LED number of lampholders 1 Display number of LED modules 1 General technical data product component Yes • light source Yes degree of pollution 1 type of voltage AC • of the operating voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage of the light source AC supply voltage of the light source AC supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz Ipauls/Outputs output voltage 1 of the lamp transformer rated value 6 V	product component front ring	Yes
color of the front ring black Holder Metal Contact block/ lampholder Socket design socket design BA 9s with LED number of lampholders 1 Display Image: Comparison of LED modules number of LED modules 1 General technical data Image: Component • lamp transformer Yes • light source Yes degree of pollution 1 type of voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz Inputs/Outputs orated value 6 V Inputs/ Outputs 6 V	design of the front ring	standard
Holder Metal Contact block/lampholder BA 9s with LED number of lampholders 1 Display 1 number of LED modules 1 General technical data 1 product component Yes • light source Yes degree of pollution 1 type of voltage AC • of the operating voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC supply voltage of the light source AC Supply voltage of the light source AC upply voltage of the light source AC Supply voltage of the light source AC	material of the front ring	metal
material of the holder Metal Contact block/ lampholder BA 9s with LED number of lampholders 1 Display 1 number of LED modules 1 General technical data 1 product component • • lamp transformer Yes • light source Yes degree of pollution 1 type of voltage AC • of the operating voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC supply voltage of the light source at AC at 60 Hz 6 V Inputs/ Outputs 6 V	color of the front ring	black
Contact block/ lampholder socket design BA 9s with LED number of lampholders 1 Display 1 number of LED modules 1 General technical data 1 type of voltage Yes e light source Yes e of the operating voltage AC e of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 e of the terminal IP20 Supply voltage of the light source at AC at 60 Hz 6 V e rated value 6 V Inputs/ Outp	Holder	
socket design BA 9s with LED number of lampholders 1 Display 1 number of LED modules 1 General technical data 1 groduct component 1 • lamp transformer Yes • light source Yes degree of pollution 1 type of voltage AC • of the operating voltage AC • of the operating voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage of the supply voltage of the light source AC supply voltage of the supply voltage of the light source AC • rated value 6 V Inputs/ Outputs 6 V	material of the holder	Metal
number of lampholders 1 Display 1 number of LED modules 1 General technical data 1 product component Yes • lamp transformer Yes • light source Yes degree of pollution 1 type of voltage AC • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage of the supply voltage of the light source AC surge of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V	Contact block/ lampholder	
Display 1 General technical data 1 general technical data 1 product component Yes • lamp transformer Yes • light source Yes degree of pollution 1 type of voltage AC • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC surge voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V	socket design	BA 9s with LED
number of LED modules 1 General technical data	number of lampholders	1
General technical data product component Iamp transformer Ves Iight source Yes degree of pollution 1 type of voltage • of the operating voltage AC surge voltage resistance rated value 4 kV protection class IP • of the terminal IP20 Supply voltage type of voltage of the light source AC supply voltage type of voltage of the light source AC supply voltage type of voltage of the light source AC supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz • rated value 6 V Inputs/ Outputs output voltage 1 of the lamp transformer rated value 6 V	Display	
product component Yes Iamp transformer Yes light source Yes degree of pollution 1 type of voltage AC • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC type of voltage of the light source AC supply voltage AC type of voltage of the light source at AC at 60 Hz 6 V Inputs/ Outputs 6 V	number of LED modules	1
• lamp transformer Yes • light source Yes degree of pollution 1 type of voltage 1 • of the operating voltage AC • of the input voltage AC • of the input voltage AC • of the input voltage IP66 • of the terminal IP20 Supply voltage AC supply voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V Inputs/ Outputs 6 V	General technical data	
• light source Yes degree of pollution 1 type of voltage 1 • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC supply voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V Inputs/ Outputs 6 V	product component	
degree of pollution 1 type of voltage AC • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC supply voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V	lamp transformer	Yes
type of voltage AC • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V Inputs/ Outputs 6 V	light source	Yes
• of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V	degree of pollution	1
• of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz AC • rated value 6 V Inputs/ Outputs 6 V	type of voltage	
surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V	 of the operating voltage 	AC
protection class IP IP66 • of the terminal IP20 Supply voltage IP20 type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz • rated value • rated value 6 V Inputs/ Outputs 6 V	 of the input voltage 	AC
• of the terminal IP20 Supply voltage AC type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V	surge voltage resistance rated value	4 kV
Supply voltage AC type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V	protection class IP	IP66
type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V	• of the terminal	IP20
supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V	Supply voltage	
• rated value 6 V Inputs/ Outputs output voltage 1 of the lamp transformer rated value 6 V	type of voltage of the supply voltage of the light source	AC
Inputs/ Outputs output voltage 1 of the lamp transformer rated value 6 V	supply voltage of the light source at AC at 60 Hz	
output voltage 1 of the lamp transformer rated value 6 V	rated value	6 V
	Inputs/ Outputs	
Connections/ Terminals	output voltage 1 of the lamp transformer rated value	6 V
	Connections/ Terminals	

type of electrical connection	screw-type terminals	
 of modules and accessories 	Screw-type terminal	
tightening torque of the screws in the bracket	20 N·m	
tightening torque [lbf-in] with screw-type terminals	8 8 lbf·in	
Lamp		
type of light source	LED	
color of the light source	yellow	
Safety related data		
touch protection against electrical shock	finger-safe	
Ambient conditions		
ambient temperature		
 during operation 	-35 +70 °C	
• during storage	-40 +85 °C	
Installation/ mounting/ dimensions		
shape of the installation opening	round	
Certificates/ approvals		
Further information		
Siemens has decided to exit the Russian market (see here).		
https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business		
Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).		
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875		
Information- and Downloadcenter (Catalogs, Brochures,)		
https://www.siemens.com/ic10		
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52BP3G9XB		
Cax online generator		
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52BP3G9XB		
Service&Support (Manuals, Certificates, Characteristics, FAQs		
https://support.industry.siemens.com/cs/ww/en/ps/US2:52BP3G9XB Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,)		
Image database (product images, 2D dimension drawings, 3D http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US		
	2.02Di 000/100/000/00	

last modified:

5/31/2021 🖸