SIEMENS

Data sheet

US2:52PA8B8E



30mm Command/52, Chrome Finish Heavy Duty,Watertight/Oiltight Complete Metal Unit Pushbutton Non-Illuminated Extended Button Plastic Cap, Orange 2 Position Momentary with 1 N.C. Late Break Heavy Duty Contacts, A600/P600 UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

Enclosure	
number of command points	1
delivery state as a kit	No
Actuator	
design of the actuating element	Pushbutton
material of the actuating element	plastic
number of contact modules	1
type of unlocking device	without
number of switching positions	2
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
General technical data	
product function positive opening	No
product component light source	No
insulation voltage rated value	600 V
surge voltage resistance rated value	4 kV
protection class IP	IP66
 of the terminal 	IP20
thermal current	10 A
operating voltage	
 at AC at 60 Hz rated value 	5 600 V
at DC rated value	5 600 V
Auxiliary circuit	
number of NC contacts for auxiliary contacts	1
number of NO contacts for auxiliary contacts	0
operational current at AC-15	
 at 110 V rated value 	60 A
at 230 V rated value	30 A
• at 400 V rated value	15 A
• at 500 V rated value	12 A
Connections/ Terminals	
type of electrical connection	screw-type terminals
tightening torque of the screws in the bracket	20 N·m
tightening torque [lbf-in] with screw-type terminals	8 lbf·in
Ambient conditions	
ambient temperature	
during operation	-35 +70 °C
during storage	-40 +85 °C

Installation/ mounting/ dimensions	
shape of the installation opening	round
mounting height	30 mm
installation width	48 mm
installation depth	35 mm
Certificates/ approvals	
Further information	
Siemens has decided to exit the Russian market (see here). https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business	
Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).	
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875	
Information- and Downloadcenter (Catalogs, Brochures,) https://www.siemens.com/ic10	
https://mail.industry.siemens.com/mail/en/en/Catalog/product?mlfb=US2:52PA8B8E	
Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PA8B8E	
Service&Support (Manuals, Certificates, Characteristics, FAQs,) https://support.industry.siemens.com/cs/ww/en/ps/US2:52PA8B8E	
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52PA8B8E⟨=en	

last modified:

6/1/2021 🖸