SIEMENS

Data sheet US2:52PP2DRB

PP2,mtd,FV 24V,FULL ILL 2NO-2NC RED



Enclosure		
number of command points	1	
delivery state as a kit	No	
Actuator		
product extension optional light source	Yes	
material of the actuating element	plastic	
number of contact modules	2	
type of unlocking device	pull-to-unlatch mechanism	
number of switching positions	2	
Front ring		
product component front ring	Yes	
design of the front ring	standard	
material of the front ring	metal	
Contact block/ lampholder		
number of lampholders	1	
Display		
number of LED modules	0	
General technical data		
product function positive opening	Yes	
product component		
lamp transformer	No	
• light source	Yes	
insulation voltage rated value	600 V	
type of voltage		
 of the operating voltage 	AC/DC	
of the input voltage	AC/DC	
surge voltage resistance rated value	4 kV	
protection class IP	IP66	
of the terminal	IP20	
thermal current	10 A	
Supply voltage		
type of voltage of the supply voltage of the light source	AC/DC	
supply voltage of the light source at AC at 60 Hz		
rated value	28 24 V	
supply voltage of the light source at DC		
rated value	28 24 V	
Auxiliary circuit		
number of NC contacts for auxiliary contacts	2	
number of NO contacts for auxiliary contacts	2	
operational current at AC-15		

 at 110 V rated value 	60 A
 at 230 V rated value 	30 A
 at 400 V rated value 	15 A
 at 500 V rated value 	12 A
Connections/ Terminals	
type of electrical connection	screw-type terminals
tightening torque of the screws in the bracket	20 N·m
tightening torque [lbf-in] with screw-type terminals	8 8 lbf·in
Lamp	
zamp	
color of the light source	clear
	clear
color of the light source	clear
color of the light source Ambient conditions	-35 +70 °C
color of the light source Ambient conditions ambient temperature	
color of the light source Ambient conditions ambient temperature • during operation	-35 +70 °C
color of the light source Ambient conditions ambient temperature	-35 +70 °C
color of the light source Ambient conditions ambient temperature • during operation • during storage Installation/ mounting/ dimensions	-35 +70 °C -40 +85 °C

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PP2DRB

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PP2DRB

 $Service \& Support \ (Manuals, \ Certificates, \ Characteristics, \ FAQs, ...)$

https://support.industry.siemens.com/cs/ww/en/ps/US2:52PP2DRB

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52PP2DRB&lang=en

last modified:	12/21/2020 🖸
----------------	--------------