## **SIEMENS**

## Data sheet

## US2:52PP2DRXB

	30mm Command/52, Chrome Finish Heavy Duty,Watertight/Oiltight Complete Metal Unit Illuminated Push-Pull Operator Full Voltage, 24V AC/DC LED Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic, Red 2 Position Maintained, Pull-to-Release UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards
design of the product	Actuator round
Enclosure	
number of command points	1
delivery state as a kit	No
Actuator	
product extension optional light source	Yes
material of the actuating element	plastic
type of unlocking device	pull-to-unlatch mechanism
number of switching positions	2
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	chrome
Holder	
material of the holder	Metal
Contact block/ lampholder	
socket design	BA 9s with LED
number of lampholders	1
Display	
number of LED modules	1
General technical data	
product component	
lamp transformer	No
light source	Yes
degree of pollution	1
type of voltage	
of the operating voltage	AC/DC
of the input voltage	AC/DC
surge voltage resistance rated value	4 kV
protection class IP	IP66
• of the terminal	IP20
operating voltage	11 20
at AC at 60 Hz rated value	24 28 V
at DC rated value	24 28 V
Supply voltage	27 20 V
type of voltage of the supply voltage of the light source	AC/DC
supply voltage of the light source at AC at 60 Hz	ACIDC
rated value	28 24 V
supply voltage of the light source at DC	2024 V
rated value	28 24 V
Connections/ Terminals	
type of electrical connection	screw-type terminals
of modules and accessories	Screw-type terminal
tightening torque of the screws in the bracket	20 N·m
tightening torque [lbf·in] with screw-type terminals	8 8 lbf·in
Lamp	
type of light source	LED

a dan af tha Babt a come	
color of the light source	red
Safety related data	
touch protection against electrical shock	finger-safe
Ambient conditions	
ambient temperature	
during operation	-35 +70 °C
during storage	-40 +85 °C
Installation/ mounting/ dimensions	
shape of the installation opening	round
Certificates/ approvals	
Further information	
https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business   Siemens is working on the renewal of the current EAC certificates.   Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).   Information on the packaging   https://support.industry.siemens.com/cs/ww/en/view/109813875   Information- and Downloadcenter (Catalogs, Brochures,)   https://www.siemens.com/ic10   Industry Mall (Online ordering system)   https://support.automation.siemens.com/mali/en/en/Catalog/product?mlfb=US2:52PP2DRXB   Cax online generator   http://support.automation.siemens.com/cs/wwien/ps/US2:52PP2DRXB   Service&Support (Manuals, Certificates, Characteristics, FAQs,)   https://support.industry.siemens.com/cs/wwien/ps/US2:52PP2DRXB   Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,)	

last modified:

5/31/2021 🖸