SIEMENS

Data sheet

US2:52PP2G3A



30mm Command/52, Chrome Finish Heavy Duty,Watertight/Oiltight Complete Metal Unit Illuminated Push-Pull Operator Transformer type, 120V AC Incandescent Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Metal, Chrome with Green Lens 2 Position Maintained, Pull-to-Release with 1 N.O. - 1 N.C. Heavy Duty Contacts, A600/P600 UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

Figure	simi	ar
--------	------	----

Enclosure			
number of command points	1		
delivery state as a kit	No		
Actuator			
product extension optional light source	Yes		
number of contact modules	1		
type of unlocking device	pull-to-unlatch mechanism		
number of switching positions	2		
Front ring	Front ring		
product component front ring	Yes		
design of the front ring	standard		
material of the front ring	metal		
Contact block/ lampholder			
number of lampholders	1		
Display			
number of LED modules	0		
General technical data			
product function positive opening	Yes		
product component			
 lamp transformer 	Yes		
light source	Yes		
insulation voltage rated value	600 V		
type of voltage			
 of the operating voltage 	AC		
 of the input voltage 	AC		
surge voltage resistance rated value	4 kV		
protection class IP	IP66		
 of the terminal 	IP20		
thermal current	10 A		
Supply voltage			
type of voltage of the supply voltage of the light source	AC		
supply voltage of the light source at AC at 60 Hz			
rated value	6 V		
Auxiliary circuit	Auxiliary circuit		
number of NC contacts for auxiliary contacts	1		
number of NO contacts for auxiliary contacts	1		
operational current at AC-15			
 at 110 V rated value 	60 A		
• at 230 V rated value	30 A		

 at 400 V rated value 	15 A	
 at 500 V rated value 	12 A	
Inputs/ Outputs		
output voltage 1 of the lamp transformer rated value	6 V	
Connections/ Terminals		
type of electrical connection	screw-type terminals	
tightening torque of the screws in the bracket	20 N·m	
tightening torque [lbf·in] with screw-type terminals	8 8 lbf·in	
Lamp		
color of the light source	clear	
Ambient conditions		
ambient temperature		
 during operation 	-35 +70 °C	
 during storage 	-40 +85 °C	
Installation/ mounting/ dimensions		
shape of the installation opening	round	
Certificates/ approvals		
Further information		
Information- and Downloadcenter (Catalogs, Brochures,)		
https://www.siemens.com/ic10		
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PP2G3A		
Cax online generator		
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PP2G3A		
Service&Support (Manuals, Certificates, Characteristics, FAQs,)		
https://support.industry.siemens.com/cs/ww/en/ps/US2:52Pf		
Image database (product images, 2D dimension drawing	gs, 3D models, device circuit diagrams, EPLAN macros,)	

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52PP2G3A&lang=en

last modified:

5/31/2021 🖸